

Technical Specification



Product Code: SIN535PWBS Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet Insert





Representative Image

General Information

Dimensions 82.5mm (W) x 82.5mm (H) x 2.5mm (D)

Insert Finish Polar White Insert With Brushed Stainless Switch

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials Insert: Polycarbonate

Rear Housing: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A
Plate Fixing Centres 60.3mm
Terminal Size 5mmø

Terminal Capacity 4 x 2.5mm², 2 x 4mm²

2.5Nm

Double Pole Yes
Ingress Protection IP20

Terminal Torque

Back Box Depth 35mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification



Product Code: SIN535PWBS Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet Insert

Compatible Cover Plates

Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D)

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate









SCP435CH



SCP435SS



SCP435BK



SCP435PW