


Technical Specification

CLICK® ScolmoreGROUP

Product Code: VPCH019WH Description: 10AX 4 Gang 2 Way Plate Switch





General Information

Dimensions 146mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Chrome

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Rocker Switch: Urea Rear Housing: Nylon

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V∼ 50Hz

Load Rating 10AX (Suitable for Inductive Loads)

Plate Fixing Centres 120.6mn
Terminal Size 3.5mmø
Terminal Torque 0.5Nm

Terminal Capacity 4 x 1.5mm² or 2 x 2.5mm²

Two Way Yes
Ingress Protection IP20

Back Box Depth 16mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensu

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.