



## **Technical Specification**

## Product Code: FPBN038BK

Description: 5A Round Pin Socket Outlet





Representative Image

## General Information

Dimensions	86mm (W) x 86mm (H) x 1.3mm (D)
Dimensions With Gasket	86mm (W) x 86mm (H) x 3mm (D)
Plate Design & Finish	Flat Plate Black Nickel
Insert Colour	Black
Materials	Front Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	5A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	1.2Nm
Terminal Capacity	4 x 1.5mm <sup>2</sup> or 3 x 2.5mm <sup>2</sup>
Switched	No
Twin Earth Terminals	No
Ingress Protection	IP20
Back Box Depth	25mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS 546: 1950
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

## Page 1 of 1 Rev.1.4 Errors & Omissions excluded. Specification is subject to change without notice.