

Technical Specification

CLICK® ScolmoreGROUP

Product Code: SIN535BKSS Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet Insert





Representative Image

General Information

 $\textbf{Dimensions} \hspace{0.5in} 82.5 \text{mm (W)} \times 82.5 \text{mm (H)} \times 2.5 \text{mm (D)} \\$

Insert Finish Black Insert With Stainless Steel Switch

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials Insert: Polycarbonate

Rear Housing: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm², 2 x 4mm²

Double Pole Yes
Ingress Protection IP20

Back Box Depth 35mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification



Product Code: SIN535BKSS Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet Insert


Compatible Cover Plates

Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D)

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate







SCP435CH



SCP435SS



SCP435BK



Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362

E: sales@scolmore.com | W: scolmore.com