

Technical Specification



Product Code: VPCH036BK Description: 13A 2 Gang Double Pole Switched Socket Outlet





Representative Image

General Information

Dimensions 146mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Chrome Insert & Gasket Colour

Black

Materials Front Plate: Stainless Steel

Insert, Switch & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 13A Plate Fixing Centres 120.6mm Terminal Size 5mmø **Terminal Torque** 2.5Nm

Terminal Capacity 4 x 2.5mm², 2 x 4mm²

Double Pole Yes Twin Earth Terminals Yes **Ingress Protection** IP20

25mm Minimum Back Box Depth Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.