

## **Technical Specification**



Product Code: MD075PW Description: 10A 3 Position Retractive Switch Module





## **General Information**

**Dimensions** 25mm (W) x 57mm (H) x 27mm (D)

Aperture Dimensions 16mm (W) x 31.5mm (H)

Finish Polar White

Materials Rocker Switch: Urea

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V 50Hz

 Load Rating
 10A

 Terminal Size
 3.5mmø

 Terminal Torque
 0.4Nm

**Terminal Capacity** 4 x 1.5mm<sup>2</sup> or 2 x 2.5mm<sup>2</sup>

Switch Contact Press to Make

Back Box Depth Dependent On Plate Used

Operational Temperature  $-5^{\circ}\text{C to } +40^{\circ}\text{C}$ 

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges