



## **Technical Specification**

## Product Code: DPSS751WH

Description: 13A Ingot Double Pole Switched Fused Connection Unit





**Representative Image** 

## **General Information**

| Dimensions              | 88mm (W) x 88mm (H) x 8mm (D)  |
|-------------------------|--|
| Dimensions With Gasket  | 91mm (W) x 91mm (H) x 9mm (D)  |
| Plate Design & Finish   | Rounded Profile Stainless Steel  |
| Insert & Gasket Colour  | White  |
| Materials               | Front Plate: Stainless Steel<br>Rear Housing: Urea<br>Switch & Fuse Drawer Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass<br>Earth Strap: Mild Steel |
| Maximum Voltage         | 250V~ 50Hz   |
| Load Rating             | 13A  |
| Plate Fixing Centres    | 60.3mm   |
| Terminal Size           | 5mmø   |
| Terminal Torque         | 2.5Nm  |
| Terminal Capacity       | 4 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>   |
| Switched                | Yes  |
| Double Pole             | Yes  |
| Twin Earth Terminals    | Yes  |
| Fuse Fitted             | 13A (BS 1362)  |
| Ingress Protection      | IP20   |
| Back Box Depth          | 25mm Minimum   |
| Operational Temperature | -5°C to +40°C  |
| Warranty                | 10 Years   |
| Standards               | BS 1363-4: 2016 +A1: 2018<br>BS 1362:1973  |

**Additional Information** 

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.