



Technical Specification

Product Code: SIN020PW

Description: 10A 3 Pole Fan Isolation Plate Switch Insert





Representative Image

G	en	era	In	TOr	ma	lion]

Dimensions	82.5mm (W) x 82.5mm (H) x 2.5mm (D)	
Insert Finish	Polar White Insert & Switch	
Cover Plate Finishes Available	BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar White) & RD (Red)	
Materials	Insert: Polycarbonate Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel	
Maximum Voltage	250V~ 50Hz	
Load Rating	10AX (Suitable for Inductive Loads)	
Plate Fixing Centres	60.3mm	
Terminal Size	3.5mmø	
Terminal Torque	0.4Nm	
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²	
Triple Pole	Yes	
Ingress Protection	IP20	
Back Box Depth	25mm Minimum	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008	
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.	

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification



Product Code: SIN020PW

Description: 10A 3 Pole Fan Isolation Plate Switch Insert

Compatible Cover Plates

Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D) Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar White) & RD (Red) Materials: Decorative: Stainless Steel, Black, Polar White & Red: Polycarbonate



SCP402BS



SCP402BK



SCP402PW



SCP402SS



Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

Page 2 of 2 Rev.1.3 Errors & Omissions excluded. Specification is subject to change without notice.