

## PVC Sleeving – 3J

PVC Sleeving to BS2848 type 3 class 85T supplied in 100m coils.  
 0.5mm wall thickness.  
 Self extinguishing -20°C to +85°C.  
 Colours available: Black, grey, blue, red, brown, white, green/yellow.  
 Size range ID: 2mm, 3mm, 4mm, 6mm, 10mm, 15mm.



## PVC Sleeve Packs – 3J

PVC Sleeving to BS2848 type 3 class 85T supplied in 5m packs.  
 0.5mm wall thickness.  
 Self extinguishing -20°C to +85°C.  
 Colours available: Black, grey, blue, red, brown, green/yellow.



PVC Size	Example	Part No.
4mm	Colour P5	<b>PVC4G/YP5</b>

## PVC Sleeving Drums – 3J

PVC Sleeving to BS2848 type 3 class 85T supplied on 100m drums.  
 0.5mm wall thickness.  
 Self extinguishing -20°C to +85°C.  
 Colours available: Black, grey, blue, brown, green/yellow.  
 Size range ID: 2mm (green/yellow only), 3mm, 4mm.



## Grommet Strip – 3K


Smooth edged LDPE Grommit strip.  
 Suitable for a range of panel thickness 0.4mm to 3mm.

Part No.	Panel thickness	Length
<b>GS1</b>	0.4 - 1.0mm	35m
<b>GS2</b>	1.1 - 1.5mm	30m
<b>GS3</b>	1.6 - 2mm	25m
<b>GS4</b>	2.1 - 3mm	20m



## Quick Fit Grommets – 3L

Push fit grommet seals are quick and easy to install, designed with a unique tapered flange to cut installation time by 50%.



Part No.		A - Panel Hole	B - Panel Thickness	C - Cable Hole
<b>GROMMET20</b>	20mm Open fast fit	19.6mm	1.9mm	15.9mm
<b>GROMMET20CLOSED</b>	20mm Closed fast fit	19.6mm	1.9mm	15.9mm
<b>GROMMET25</b>	25mm Open fast fit	24.8mm	2.1mm	19.6mm
<b>GROMMET25CLOSED</b>	25mm Closed fast fit	24.8mm	2.1mm	19.6mm
<b>GROMMET32</b>	32mm Open fast fit	32mm	1.6mm	23.8mm
<b>GROMMET32CLOSED</b>	32mm Closed fast fit	32mm	1.6mm	23.8mm
<b>GROMMET38</b>	38mm Open	38mm	1.6mm	31.8mm
<b>GROMMET38CLOSED</b>	38mm Closed	38mm	1.6mm	31.8mm
<b>GROMMET50</b>	50mm Open	50mm	1.6mm	44.4mm
<b>GROMMET50CLOSED</b>	50mm Closed	50mm	1.6mm	44.4mm