

Extreme Cable Ties – 10A

Our premium range of ties manufactured from virgin 6/6 nylon.
 -40°C to +85°C.
 UV resistant to ISO4892.
 UL94V2 flammability rating.
 SGS, RINA, Lloyd, UL, Sincert and dnv certified.
 Halogen free and Rohs Competent



Approved by



Part No.						
EXTT100-2.5	EXTT140-3.6	EXTT160-2.5	EXTT200-2.5	EXTT200-3.6	EXTT300-3.6	EXTT160-4.8
EXTT200-4.8	EXTT250-4.8	EXTT300-4.8	EXTT370-4.8	EXTT430-4.8	EXTT200-7.8	EXTT300-7.8
EXTT370-7.8	EXTT540-8	EXTT750-8	EXTT1000-8	EXTT500-13		

Nylon 6/6 Cable Ties – 10A

Nylon 6/6 cable tie.
 High resistance to bases, oils, greases and chloride solvents.
 -40°C to +85°C.
 UL94V2.
 Ordering code:
 TT - Length (mm) - Width (mm) - Colour (Nat/Black)



Part No.						
TT100-2.5	TT140-3.6	TT160-2.5	TT200-2.5	TT200-3.6	TT300-3.6	TT160-4.8
TT200-4.8	TT250-4.8	TT300-4.8	TT370-4.8	TT430-4.8	TT200-7.8	TT300-7.8
TT370-7.8	TT540-8	TT750-8	TT1000-8	TT500-13		

LSF Cable Ties – 10B

Nylon 6/6.
 UL94V0.
 Low smoke cable tie.
 Available in black only.
 -40°C to +85°C.
 Halogen free resins.
 High resistance to oils, greases, oil derivatives, chloride solvents.

Part No.	Length mm	Width mm
TT200-4.8LSF	200	4.8
TT300-4.8LSF	300	4.8
TT370-4.8LSF	370	4.8
TT370-7.8LSF	370	7.8
TT540-7.8LSF	540	7.8
TT750-8LSF	750	8.0

