

# AP & APS Cable Clips + Saddles – 5B

Clips and saddles designed for mineral insulated and soft skin fire cables.  
 Manufactured from copper with a Plascoat PPA 571 coating. London Underground approved.



Part No. P CLIP	Min/Max cable range mm
AP7	7 - 7.4
AP8	7.5 - 9.1
AP9	9.1 - 10
AP10	10.1 - 10.7
AP11	10.6 - 11.7

Part No. 2 WAY SADDLE	Min/Max cable range mm
AP7S	7 - 7.4
AP8S	7.8 - 9
AP9S	9.1 - 9.7
AP10S	9.8 - 10.7

# RC Bare Clips – 5B

A range of bare clips and saddles are also available.

Part No.
RC22
RC24

Part No.
RC26
RC28

Part No.
RC30
RC32

Part No.
RC40



# RMX Compound – 5B

Designed to seal against water and general weather.  
 This compound is used in potting RPS mineral insulated seals.  
 Remains in a pliable state.  
 Temperature range: +150°C max.



# Trunking Fire Clips – 5B

Clip for plastic trunking rated to 930°C for 2 hours to BS7621.

Part No.	Size
CLIP30	25mm trunking



# Concrete Fixing Screw – 5B

Direct fix concrete screw.

Part No.	Size
CONC-SCREW	5.5mm x 45mm

