

Spryte™

Fixed/Adjustable Integrated Polycarbonate LED Downlights

- Designed for residential applications
- ThermoTec™ heat management technology
- Sparkling low glare multifaceted EnFiniti™ lens
- Delivering up to 105lm/W
- Halogen like optical appearance in a compact sized fitting
- 60° beam angle for uniform light distribution
- Pre-wired with 500mm 2 core cable
- IP44 rated
- Supplied with integrated LED driver

make smart with



See pg.256-258 for compatibility table

3 Year Warranty

L70 25,000hrs

Triac dimmable option

Matt White finish

make smart with




works with

.control



Triac In-Line Dimmer
See pg.41



Smart Rotary Dimmer
See pg.35



On/Off Relay
See pg.47



8W Fixed



10W Fixed




8W Adjustable


EN-DDL1019
Supplied with interchangeable
Square & Round Bezels



EN-DL10160



Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cutout [Ø]
Non-Dimmable Fixed						
EN-DL10160/30	8W	3000K	620lm	78	60°	60mm
EN-DL10160/40	8W	4000K	680lm	85	60°	60mm
Triac Dimmable Fixed						
EN-DDL10160/30	8W	3000K	620lm	78	60°	60mm
EN-DDL10160/40	8W	4000K	680lm	85	60°	60mm
Triac Dimmable Adjustable						
EN-DDL10260/30	8W	3000K	620lm	78	60°	70mm
EN-DDL10260/40	8W	4000K	680lm	85	60°	70mm
Triac Dimmable High Output Fixed						
EN-DDL1019/30	10W	3000K	1000lm	100	60°	82mm
EN-DDL1019/40	10W	4000K	1050lm	105	60°	82mm



EN-DL10160

(H) 56mm Height
(OD) 78mm Overall (Ø)

EN-DDL10160

(H) 56mm Height
(OD) 78mm Overall (Ø)

EN-DDL10260

(H) 55mm Height
(OD) 90mm Overall (Ø)

EN-DDL1019

(H) 57mm Height
(OD) 105mm Overall (Ø)