

# COMMERCIAL CAESAR LED BATTEN




## CAESAR LED BATTEN, WHITE


- Suitable for use in offices, corridors, stairways, retail shops, health centres, storage areas, work stations, hotels, schools
- Wide operating ambient temperature range of -20 °C to +40 °C
- Emergency version operates for 3 hour duration, c/w test switch
- Large terminals allowing easy loop-in/ loop-out
- C/w mounting accessories and suspension kit allowing suspending at max 1m
- Suitable for analogue, DALI, and switch dimming
- Complies with requirements of the Energy Technology Criteria List. Enhanced Capital Allowances may be claimed on the cost of the luminaires, installation and transport to site



### CONVERSIONS AVAILABLE




DIMENSIONS(mm)	Width	Length	Height
RCA244006-01	62	560	74
RCA244012-01	62	1,160	74
RCA484012-01	62	1,160	74
RCA484015-01	62	1,460	74
RCA804015-01	62	1,460	74
RCA604018-01	62	1,723	74
RCA964018-01	62	1,723	74



# COMMERCIAL CAESAR LED BATTEN

	0.6M	1.2M	1.2M	1.5M	1.5M
Neutral White	24W	24W	48W	48W	80W
Standard	<b>RCA244006-01</b>	<b>RCA244012-01</b>	<b>RCA484012-01</b>	<b>RCA484015-01</b>	<b>RCA804015-01</b>
Emergency		<b>RCA244012E-01</b>	<b>RCA484012E-01</b>	<b>RCA484015E-01</b>	<b>RCA804015E-01</b>
<b>Comparable to:</b>	2 x 18W	1 x 36W	2 x 36W	1 x 58W	2 x 58W
<b>Total Power (W):</b>	23.1	23.0	46.0	45.8	78.5
<b>Total Light Output (lm):</b>	2,660 standard	2,850 standard 410 emergency	5,320 standard 410 emergency	5,400 standard 410 emergency	8,720 standard 400 emergency
<b>Efficacy (lm/cctW):</b>	115	124	116	118	111
<b>Lifetime (hrs):</b>	50,000	50,000	50,000	50,000	50,000
<b>Beam Angle (deg):</b>	140	140	140	140	140
<b>Lux at 1m (lux):</b>	730 standard	770 standard 110 emergency	1,440 standard 110 emergency	1,460 standard 110 emergency	2,320 standard 110 emergency
<b>CCT (K):</b>	4000	4000	4000	4000	4000
<b>CRI (Ra):</b>	80	80	80	80	80
<b>Power Factor (PF):</b>	0.95	0.95	0.97	0.97	0.97
<b>Impact Rating (IK):</b>	08	08	08	08	08
<b>Weight (kg):</b>	0.78	2.1/2.4	2.1/2.5	2.5/3.0	2.5/3.1

	1.8M	1.8M
Neutral White	60W	96W
Standard	<b>RCA604018-01</b>	<b>RCA964018-01</b>
<b>Comparable to:</b>	1 x 70W	2 x 70W
<b>Total Power (W):</b>	56.4	96.4
<b>Total Light Output (lm):</b>	7,140 standard	11,260 standard
<b>Efficacy (lm/cctW):</b>	127	117
<b>Lifetime (hrs):</b>	50,000	50,000
<b>Lux at 1m (lux):</b>	1,900	3,150
<b>Beam Angle (deg):</b>	140	140
<b>CCT (K):</b>	4000	4000
<b>CRI:</b>	80	80
<b>Impact Rating (IK):</b>	08	08
<b>Power Factor (PF):</b>	0.97	0.97
<b>Weight (kg):</b>	3.1	3.2



ECA eligible  
SEAI approved

