

SURFACE FITTINGS

HAWK LED




HAWK LED SURFACE FITTING

- A high security, anti-tamper companion to the EAGLE range
- Common aesthetic across the HAWK range allows mix and match of fittings in the building of different lumen packages size
- Wide operating ambient temperature range of -20°C to +35°C
- Screw-on trim fitted with retained anti-tamper TORX T20 security screws and requires matching screwdriver head to release and replace trim
- Complies with requirements of the Energy Technology Criteria List. Enhanced Capital Allowances may be claimed on the cost of the luminaires, installation and transport to site
- Screw-on trim fitted with retained anti-tamper TORX T20 security screws and requires matching screwdriver head to release and replace trim

ACCESSORIES


RHKMTRIM-04	Black Trim
RHKMTRIM-24	Grey Trim
RHKMEY-04	Black Eyelid Trim
RHKMCR-24	Grey Eyelid Trim
RHKMCR-04	Black Cross Grid Trim
RHKMCR-24	Grey Cross Grid Trim
RHKMCOLL-01	Medium Extension Collar, White

CONVERSIONS AVAILABLE



DIMENSIONS(mm)

DIMENSIONS(mm)	Diameter	Height
10W	330	91
14W	330	91
25/35W	420	91



SURFACE FITTINGS

HAWK LED



HAWK Base



Anti-tamper, screw-on trim

	10W	14W	25/35W
Standard	RHKM01040-01	RHKM01540-01	RHKLDP40-01
Emergency	RHKM01040E-01	RHKM01540E-01	RHKLDP40E-01
Microwave Sensor	RHKM01040-01SEN	RHKM01540-01SEN	
Emergency & Sensor	RHKM01040E-01SEN	RHKM01540E-01SEN	
Comparable to:	28W PL	38W PL	55/2X38W PL
Total Power (W):	9.6	12.7	21.4/34.4
Total Light Output (lm):	1,050 standard 120 emergency	1,400 standard 160 emergency	2340/4020 standard 250/310 emergency
Efficacy (lm / cctW):	109	110	109/117
Lifetime (hrs):	50,000	50,000	50,000
Beam Angle (deg):	110	110	110
Illuminance at 1m (lx):	340 standard 50 emergency	450 standard 80 emergency	780/1330 standard 85/100 emergency
CCT (K):	4000	4000	4000
CRI (Ra):	80	80	80
Impact Rating (IK):	10	10	10
Power Factor (PF):	0.95	0.95	0.97
Box Qty:	1	1	1
Weight (kg):	1.28 standard 1.54 emergency	1.28 standard 1.54 emergency	1.56 standard 1.82 emergency



LIA Verified
ECA eligible
SEAI Approved

