

Tee with inside lid and gusset

Fixing Options: Turnbuckle type e.g. TIT/100/100/PG/G

Screw fix type – add “S” after the first T e.g. TSIT/100/100/PG/G

Tamper proof type – add “M” after the first T e.g. TMIT/100/100/PG/G



| Width mm | 50mm Deep | 75mm Deep | 100mm Deep | 150mm Deep | 225mm Deep | 300mm Deep |
|----------|------------------|------------------|------------------|------------------|------------------|------------------|
| 50 | TIT/050/050/PG/G | N/A | N/A | N/A | N/A | N/A |
| 75 | TIT/075/050/PG/G | TIT/075/075/PG/G | N/A | N/A | N/A | N/A |
| 100 | TIT/100/050/PG/G | TIT/100/075/PG/G | TIT/100/100/PG/G | N/A | N/A | N/A |
| 150 | TIT/150/050/PG/G | TIT/150/075/PG/G | TIT/150/100/PG/G | TIT/150/150/PG/G | N/A | N/A |
| 225 | TIT/225/050/PG/G | TIT/225/075/PG/G | TIT/225/100/PG/G | TIT/225/150/PG/G | TIT/225/225/PG/G | N/A |
| 300 | TIT/300/050/PG/G | TIT/300/075/PG/G | TIT/300/100/PG/G | TIT/300/150/PG/G | TIT/300/225/PG/G | TIT/300/300/PG/G |

Tee with outside lid and gusset

Fixing Options: Turnbuckle type e.g. TOT/100/100/PG/G

Screw fix type – add “S” after the first T e.g. TSOT/100/100/PG/G

Tamper proof type – add “M” after the first T e.g. TMOT/100/100/PG/G



| Width mm | 50mm Deep | 75mm Deep | 100mm Deep | 150mm Deep | 225mm Deep | 300mm Deep |
|----------|------------------|------------------|------------------|------------------|------------------|------------------|
| 50 | TOT/050/050/PG/G | N/A | N/A | N/A | N/A | N/A |
| 75 | TOT/075/050/PG/G | TOT/075/075/PG/G | N/A | N/A | N/A | N/A |
| 100 | TOT/100/050/PG/G | TOT/100/075/PG/G | TOT/100/100/PG/G | N/A | N/A | N/A |
| 150 | TOT/150/050/PG/G | TOT/150/075/PG/G | TOT/150/100/PG/G | TOT/150/150/PG/G | N/A | N/A |
| 225 | TOT/225/050/PG/G | TOT/225/075/PG/G | TOT/225/100/PG/G | TOT/225/150/PG/G | TOT/225/225/PG/G | N/A |
| 300 | TOT/300/050/PG/G | TOT/300/075/PG/G | TOT/300/100/PG/G | TOT/300/150/PG/G | TOT/300/225/PG/G | TOT/300/300/PG/G |

Crossovers & Reducers

Crossovers

Fixing Options: Turnbuckle type e.g. TCO/100/100/PG/G

Screw fix type – add “S” after the first T e.g. TSCO/100/100/PG/G

Tamper proof type – add “M” after the first T e.g. TMCO/100/100/PG/G



| Width mm | 50mm Deep | 75mm Deep | 100mm Deep | 150mm Deep | 225mm Deep | 300mm Deep |
|----------|------------------|------------------|------------------|------------------|------------------|------------------|
| 50 | TCO/050/050/PG/G | N/A | N/A | N/A | N/A | N/A |
| 75 | TCO/075/050/PG/G | TCO/075/075/PG/G | N/A | N/A | N/A | N/A |
| 100 | TCO/100/050/PG/G | TCO/100/075/PG/G | TCO/100/100/PG/G | N/A | N/A | N/A |
| 150 | TCO/150/050/PG/G | TCO/150/075/PG/G | TCO/150/100/PG/G | TCO/150/150/PG/G | N/A | N/A |
| 225 | TCO/225/050/PG/G | TCO/225/075/PG/G | TCO/225/100/PG/G | TCO/225/150/PG/G | TCO/225/225/PG/G | N/A |
| 300 | TCO/300/050/PG/G | TCO/300/075/PG/G | TCO/300/100/PG/G | TCO/300/150/PG/G | TCO/300/225/PG/G | TCO/300/300/PG/G |

Reducers

Fixing Options: Turnbuckle type e.g. TTR/100/100/TO/050/050/PG

Screw fix type – add “S” after the first T e.g. TSTR/100/100/TO/050/050/PG

Tamper proof type – add “M” after the first T e.g. TMTR/100/100/TO/050/050/PG3



| Width 1 mm | Width 2 mm | | | |
|------------|---------------------------|---------------------------|---------------------------|---------------------------|
| | 50 x 50 | 75 x 75 | 100 x 100 | 150 x 150 |
| 75 x 75 | TTR/075/075/TO/050/050/PG | N/A | N/A | N/A |
| 100 x 100 | TTR/100/100/TO/050/050/PG | TTR/100/100/TO/075/075/PG | N/A | N/A |
| 150 x 150 | TTR/150/150/TO/050/050/PG | TTR/150/150/TO/075/075/PG | TTR/150/150/TO/100/100/PG | N/A |
| 225 x 225 | TTR/225/225/TO/050/050/PG | TTR/225/225/TO/075/075/PG | TTR/225/225/TO/100/100/PG | TTR/225/225/TO/150/150/PG |
| 300 X 300 | TTR/300/300/TO/050/050/PG | TTR/300/300/TO/075/075/PG | TTR/300/300/TO/100/100/PG | TTR/300/300/TO/150/150/PG |