



150mm Window Fixing Kit
for
SDF150 Range

SDF911WFK

Fitting Instructions

It is strongly advised that mounting the kit is a two person operation.

Hole size required: 185mm diameter.

Glazing thickness 16mm-30mm

1. Remove the two screws from gravity-flap grille (top and bottom) and remove the gravity-flap grille.
2. Unscrew the four brass barrel nuts and retain.
3. Separate the gravity-flap housing moulding from the window-spacer moulding. Insert the four self-tapping screws, provided with this kit, into the window spacer moulding and then remove -
- Do this by pre-cutting the threads in the moulding at this point as it will avoid undue strain on the window glass later.
4. Gently press the foam seal strip into the moulded grooves of gravity-flap housing to form a watertight weather seal.
5. Clean the window glass before assembly.
6. Feed supply cable into the window-spacer.
7. From outside, push the gravity-flap housing through the hole in the glass, making sure the sign "UP" is located in right direction.
8. From inside, gently fit the window-spacer over four studs, making sure the sign "UP" is located in right direction.
9. Secure two parts together with four brass barrel nuts, taking care to not over strain the glass. The brass barrel nuts have a screwdriver slot to assist in this operation.
10. Place the gravity-flap over housing and secure with screws (top and bottom).
11. The fan can now be fitted to the window-spacer using four self-tapping screws supplied.
12. Take care to follow the instruction supplied with the fan to complete the installation.

Domus Ventilation Block C
Caerphilly Business Park
Caerphilly
CF83 3ED
UK Tel 03443 715 523
UK Fax 03443 715 524

International tel: +44 (0)1302 348878
International fax: +44 (0)1302 348879
Email: vent.info@domusventilation.co.uk
Web: www.domusventilation.co.uk
LAB988R Issue 1, Nov 2017

