

**FEATURES AND USES**

Suitable for indoor and outdoor use  
 Body depth suitable for 20mm cable entry with cable gland or conduit.  
 Power terminals large enough for loop-in / loop-out connections  
 Grey polycarbonate body with red or opal diffuser options  
 Comes with integrated LED tray - no lamp required  
 2 Year Warranty

**FEATURES AND USES**

Suitable for use on site and in industrial and commercial applications  
 Impact resistant polycarbonate diffuser and base on bulkhead  
 Supplied maintained and can be wired non-maintained  
 Constant light output when operating on mains or battery power  
 Can be used as both a temporary light fitting or permanent  
 Comes with integrated LED tray  
 1 Year Warranty



Product Code	Colour	Wattage	Lumen Output	IK Rating	IP Rating	CCT (K)	Colour Temp	Voltage	Beam Angle	Rated Life
B2010	Opal	8W	640lm	IK08	IP65	6000K	Daylight	100-277V AC 50/60Hz	120°	20,000hrs
B2020	Red	8W	640lm	IK08	IP65	6000K	Daylight	100-277V AC 50/60Hz	120°	20,000hrs

Product Code	Wattage	Lumen Output	IK Rating	IP Rating	CCT (K)	Colour Temp	Voltage	Beam Angle	Rated Life
E9600	3W	120lm	IK04	IP65	6000K	Daylight	110V AC	120°	35,000hrs