



## elite 3 trunking key features




- 175mm x 60mm profile
- Aesthetically pleasing curved design
- Manufactured from high impact resistant uPVC compound
- Suitable for Dado or Skirting mounting either vertically or horizontally
- Pre-punched base
- Large pre-punched knockouts located on both internal walls
- Full range of fittings and accessories
- Attractive two piece adjustable Internal & External covers to accommodate walls that do not have a true 90 degree
- Internal and External Angles maintain necessary bend radius to comply with CAT5E, CAT6, Shielded, CAT7 and CAT6A 10 gig solutions
- Moulded Flat Tee and Flat Angle with data guide to maintain necessary bend radius and cable segregation
- Moulded Flat Tee and Flat Angle overlap Trunking to prevent need of additional Joint Covers
- Screw fit fittings available (optional)
- 1 & 2 Gang 50mm boxes with large knockouts
- Pre-punched Steel Screen Divider (BSEN50174-2)
- DDA Compliancy obtainable
- ROHS Compliant
- ELITE 3 Hygieia Range available – antimicrobial protection
- Available as pre-assembled units

# elite 3 trunking technical information



## dimensions and cable capacities



DATA CABLE DIAMETER (mm)	NOMINAL CSA (mm <sup>2</sup> )	COMPARTMENT A 2070mm <sup>2</sup>	COMPARTMENT B			COMPARTMENT C 2070mm <sup>2</sup>
			3590mm <sup>2</sup>	3590mm <sup>2</sup> and 25mm BOX	3590mm <sup>2</sup> and 35mm BOX	
		45% Fill (928mm <sup>2</sup> )	45% Fill (1615mm <sup>2</sup> )	45% Fill (813mm <sup>2</sup> )	45% Fill (488mm <sup>2</sup> )	45% Fill (928mm <sup>2</sup> )
5	19.6	47	82	41	24	47
5.5	23.8	38	67	34	20	38
6	28.3	32	57	28	17	32
6.5	33.2	28	48	24	14	28
7	38.5	24	41	21	12	24
8	50.3	18	32	16	9	18
9	63.6	14	25	12	7	14
10	78.5	11	20	10	6	11
POWER CABLE CONDUCTOR CSA (mm <sup>2</sup> )	CABLE FACTOR	COMPARTMENT A 1040mm <sup>2</sup>	COMPARTMENT B			COMPARTMENT C 1040mm <sup>2</sup>
			3590mm <sup>2</sup>	3590mm <sup>2</sup> and 25mm BOX	3590mm <sup>2</sup> and 35mm BOX	
		45% Fill (468mm <sup>2</sup> )	45% Fill (1615mm <sup>2</sup> )	45% Fill (813mm <sup>2</sup> )	45% Fill (488mm <sup>2</sup> )	45% Fill (928mm <sup>2</sup> )
1.5	8.6	107	187	98	61	107
2.5	12.6	73	126	67	41	73
4	16.6	55	97	51	31	55
6	21.2	43	76	40	25	43

Typical cable loading information in line with wiring regulation BS 7671 (45% CSA Fill)

**STANDARDS** - ELITE 3 Trunking system meets and exceeds the requirements for:  
BS6701, ISO/IEC11801(ED2.0 Amd 2) and Cenelec (BSEN50173 Part 1/2, BSEN50174-2) BS4678 Pt 4, BS7671 (IEE regs)



# elite 3 trunking accessories



ME3



ME3F



ME3T



ME3I



ME3E



ME3C



ME3J



ME3SD



ME3SDE



MTDDA1 (BL-CH-LG)



MTDDA2 (BL-CH-LG)



MTLS

# elite 3 trunking accessories




**ME3TOA**



**ME3RCDH**



**MTSB1, MTSB1-4,  
MTSB1-25, MTSB1-25-4,  
MTSB1-50**



**MTSB1-F**



**MTSB2, MTSB2-25  
MTSB2-50**



**MTSB2-F**



**SECURITY FITTINGS**

CODE	DESCRIPTION	PACK SIZE
<b>ME3</b>	Marco ELITE 3 Trunking 175 x 60mm	2 x 3m
<b>ME3F</b>	Flat angle	1
<b>ME3T</b>	Flat tee	1
<b>ME3I</b>	Internal adjustable angle	1
<b>ME3E</b>	External adjustable angle	1
<b>ME3C</b>	End cap	2
<b>ME3J</b>	Joint cover	5
<b>ME3SD</b>	Steel screen divider	4 x 1.5m
<b>ME3SDE</b>	ELITE 3 external angle screening divider	1
<b>MTDDA1 (BL-CH-LG)</b>	Coloured back plate 1-gang	10
<b>MTDDA2 (BL-CH-LG)</b>	Coloured back plate 2-gang	10
<b>MTLS</b>	Accessory spacer	10
<b>ME3TOA</b>	Take off adaptor	1
<b>ME3RCDH</b>	RCD/MCB DIN rail housing (includes: hinged cover, mounting frame, mounting bracket, Marco locking mechanism available)	1
<b>MTSB1</b>	Socket mounting box 35mm 1-gang	10
<b>MTSB1-4</b>	Socket mounting box 35mm 1-gang 4 pillar	10
<b>MTSB1-25</b>	Socket mounting box 25mm 1-gang	10
<b>MTSB1-25-4</b>	Socket mounting box 25mm 1-gang 4 pillar	10
<b>MTSB1-50</b>	Socket mounting box 50mm 1-gang	10
<b>MTSB1-F</b>	1-gang socket mounting frame	10
<b>MTSB2</b>	Socket mounting box 35mm 2-gang	10
<b>MTSB2-25</b>	Socket mounting box 25mm 2-gang	10
<b>MTSB2-50</b>	Socket mounting box 50mm 2-gang	10
<b>MTSB2-F</b>	2-gang socket mounting frame	10
<b>SECURITY FITTINGS</b>	Please add suffix - SF to the standard catalogue number	