



Perfect for.....
The solution to drilling in nail embedded Wood



- A** 1/4" quick-change shank* for added convenience and rapid diameter tool change. Impact rated for impact drivers.
- B** Four deep auger style flutes for rapid chip evacuation and faster drilling speeds
- C** Four precision ground cutting teeth for extreme drilling comfort and balance
- D** Robust cutting tooth profile provides **extreme resistance to hard objects such as nails**
- E** High Speed Steel cutting head increases **durability in tough materials for longer life**

*Apart from 32mm which has a 7/16" shank & can't be used in impact drivers

STUBBY LENGTH
Ideal for Joists

The 120mm Stubby Is Ideal for:

- Inter-joist drilling
- Working in tight spaces
- Users with larger drilling machines

The Nail-Proof WoodBeaver is ideal for:

- Drilling nail embedded Wood
- Inter-joist drilling
- Producing cable / pipe passages through timber etc



The Nail-Proof WoodBeaver can be used in:

- Nail embedded Wood
- Softwoods
- Hardwoods
- Veneered chipboard
- Plywood
- Chipboard

Scan me for demo video



TECH TIP!

Up to 25mm diameter can be used within an impact driver. This gives the advantages of one-handed operation and improved access in tight spaces

Nail-Proof WoodBeaver

Diameter Size mm	Overall Length mm	Working Length mm	Part Number
16	165	125	WWBNP16
20	165	125	WWBNP20
22	165	125	WWBNP22
25	165	125	WWBNP25
32	165	125	WWBNP32



Nail-Proof Stubby WoodBeaver

Diameter Size mm	Overall Length mm	Working Length mm	Part Number
16	120	80	WWBNPST16
20	120	80	WWBNPST20
22	120	80	WWBNPST22
25	120	80	WWBNPST25
32	120	80	WWBNPST32




4 Piece Nail-Proof Stubby Set

Description	Set Contents	Part Number
4 Piece Nail-Proof Stubby Set	1 X 16 / 20 / 25mm 1 X Quick-Change SDS Plus to 1/4" Adaptor	WWBNP4PCSET



WoodBeaver Accessories

	Drive Type	Length mm	Internal mm	Technical Product Detail	Part Number
Quick-Change SDS Plus to 1/4" Adaptor <small>*Twister Impact rated for impact drivers</small>	SDS Plus	60	1/4"	For Sizes 10 - 25mm	SDS1/4WB055
7/16" SDS Plus drive adaptor	SDS Plus	90	7/16"	For Sizes 32mm only	SDS7/16WB090
Quick-Change 1/4" Extension Rod <small>*Twister Impact rated for impact drivers</small>	1/4" Hexagon	230	1/4"	For Sizes 10 - 25mm	WWB1/4HEX250



32mm WoodBeavers have min. chuck requirement of 13mm

1/4" shank (except 32mm WoodBeavers)

7/16" shank (32mm WoodBeaver only)

When used with relevant adaptor

M6x6 (7/16" adaptor grubscrews)

7/16" adaptor grubscrews

Up to 25mm only