

Loadbank 250 Selection Chart - 400A Panel Board Circuit Protection Devices

Incoming Devices			
Current rating (A)		3-pole cat. no.	4-pole cat. no.
Max.	Min.		
YA3 switch disconnecter			
250	-	YA3B3P250D	YA3B4P250D
YA3 frame MCCB - 25kA			
250	160	YA3N3P250T	YA3N4P250T
YA3 frame MCCB - 36kA			
250	160	YA3S3P250T	YA3S4P250T
Y6 switch disconnecter			
400	-	Y6B3P400D	Y6B4P400D
Y6 frame MCCB - 50kA			
400	250	Y6H3P400T5	Y6H4P400T5
200A skeleton switches			
200	-	SF3P200N	SF4P200
400A skeleton switches			
400	-	SL3P400N	SL4P400
400A direct connection			
400	-	-	LBDR4

Outgoing Devices for Form 2 Panel Boards		
Current rating (A)	1-pole cat. no.	3-pole cat. no.
Max.		
YA3 MCCB - 25kA		
16	YA3N1P16T	-
20	YA3N1P20T	YA3N3P20T
32	YA3N1P32T	YA3N3P32T
40	YA3N1P40T	-
50	YA3N1P50T	YA3N3P50T
63	YA3N1P63T	YA3N3P63T
80	YA3N1P80T	-
100	YA3N1P100T	YA3N3P100T
125	YA3N1P125T	YA3N3P125T
160	YA3N1P160T	YA3N3P160T
200	-	YA3N3P200T
250	-	YA3N3P250T
YA3 MCCB - 36kA		
20	-	YA3S3P20T
32	-	YA3S3P32T
50	-	YA3S3P50T
63	-	YA3S3P63T
100	-	YA3S3P100T
125	-	YA3S3P125T
160	-	YA3S3P160T
200	-	YA3S3P200T
250	-	YA3S3P250T