

CABLE GLANDS & ACCESSORIES



Brass gland kits

- 20-32mm kits include 2 glands, 2 shrouds, 2 tags and 2 locknuts.

- 40+ mm kits include 1 of each.

Washers for Glands

To improve anti-vibration and IP rating, please see fibre, nylon & shakeproof washers on page 2.

* Test certificates and certificates of conformity can be supplied if requested



BW INDUSTRIAL BRASS CABLE GLAND

2 part brass gland with knurled entry suitable for steel wired armoured cables (SWVA). Provides mechanical cable retention & electrical continuity.

Standard: BS EN 50262
Ingress Protection: IP2X EN 60529 – Indoor use
Clamping – 2 part armour lock
Protection Material: Brass BS2874
Operating Temperature: -80°C to +300°C

Code	Kit Qty	Size	
BW20S	2 per kit	20mm SMALL	
BW20	2 per kit	20mm	
BW25	2 per kit	25mm	
BW32	2 per kit	32mm	
BW40	1 per kit	40mm	
BW50	1 per kit	50mm	
BW63	1 per kit	63mm	
BW75	1 per kit	75mm	



CW INDUSTRIAL BRASS CABLE GLAND

3 part brass gland suitable for steel wired armoured cables (SWA) Provides an environmental seal on the outer sheath and also mechanical cable retention & electrical continuity.

Standard: BS EN 50262
Ingress Protection: IP66 – dust tight and protected against powerful water jets
Clamping – 2 part armour lock
Protection Material: Brass BS2874 Seal: TPE (Thermoplastic Elastomeric)
Operating Temperature: -20°C to +80°C

Code	Kit Qty	Size	
CW20S	2 per kit	20mm SMALL	
CW20	2 per kit	20mm	
CW25	2 per kit	25mm	
CW32	2 per kit	32mm	
CW40	1 per kit	40mm	
CW50	1 per kit	50mm	



CXT INDUSTRIAL BRASS CABLE GLAND

2 part brass gland suitable for wire braid / wire braid armour cables (CY, SY type) Provides an environmental seal on the outer sheath and also mechanical cable retention & electrical continuity.

Standard: BS EN 50262
Ingress Protection: IP66 – dust tight and protected against powerful water jets
Clamping – unique integral of teased braids
Protection Material: Brass BS2874
Operating Temperature: -20°C to +80°C

Code	Kit Qty	Size	
CXT20S	2 per kit	20mm SMALL	
CXT20	2 per kit	20mm	
CXT25	2 per kit	25mm	
CXT32	2 per kit	32mm	
CXT40	1 per kit	40mm	
CXT50	1 per kit	50mm	



E1W INDUSTRIAL BRASS CABLE GLAND

2 part brass gland suitable for steel wired armoured cables (SWA) Providing environmental seal on both the Cable Inner & Outer Sheaths so can be used in more hazardous areas. Also provides mechanical retention & electrical continuity.

Standard: BS EN 50262
Ingress Protection: IP66 – dust tight and protected against powerful water jets
Clamping – Detachable armoured Cone & outer clamping Ring
Protection Material: Brass BS2874
Operating Temperature: -20°C to +80°C

Code	Kit Qty	Size	
E1WS20S	2 per kit	20mm SMALL	
E1WS20	2 per kit	20mm	
E1WS25	2 per kit	25mm	
E1WS32	2 per kit	32mm	
E1WS40	1 per kit	40mm	
E1WS50	1 per kit	50mm	



A2 INDUSTRIAL BRASS CABLE GLAND

2 part brass gland suitable for un-armoured cables The outer seal grips the sheath of the cable to achieve a weatherproof seal.

Standard: BS EN 50262
Ingress Protection: IP65 – dust tight and protected against water jets
Clamping – outer displacement seal
Protection Material: Brass BS2874
Operating Temperature: -20°C to +80°C

Code	Kit Qty	Size	
A220S	2 per kit	20mm SMALL	
A220	2 per kit	20mm	
A225	2 per kit	25mm	
A232	2 per kit	32mm	
A240	1 per kit	40mm	
A250	1 per kit	50mm	