

# Loadlimiter 63 Selection Chart - A-type

## Distribution Boards

Busbar rating	Outgoing ways	Width (mm)	Weight (kg)	Cat. no.
125A	6	270	3.8	DA06X
125A	9	323	4.3	DA09X
125A	12	377	4.8	DA12X
125A	15	430	5.3	DA15X
125A	18	484	6.0	DA18X
125A	22	555	7.0	DA22X

## Service Centres

For DIN-rail modules	Modular ways			
Service centre	8	270	3.8	DAS08X
Service centre	11	323	4.3	DAS11X
Service centre	14	377	4.8	DAS14X
Service centre	17	430	5.3	DAS17X
Service centre	20	484	6.0	DAS20X
Service centre	24	555	7.0	DAS24X

## Incoming Devices

Device type	Current rating (A)	Sensitivity (mA)	Max. cable (mm <sup>2</sup> )	
Switch disconnecter	100	-	50	AV2100
Switch disconnecter	125	-	50	AV2125
RCCB, type AC	63	30	35	EE63/30/2
RCCB, type AC	63	100	35	EE63/100/2
RCCB, type AC	63	300	35	EE63/300/2
RCCB, type AC	80	30	35	EE80/30/2
RCCB, type AC	100	30	35	EE100/30/2
RCCB, type AC	100	100	35	EE100/100/2
RCCB type AC time delay	100	100	35	EES100/100/2
Direct connection	-	-	35	DBXD0
Direct connection	-	-	70	DAXD1

## Surge Protection

SP + NE surge protection	DSPM1PN
MOV replacement plug-in module	DSPML
MOV neutral/earth replacement plug-in module	DSPMNE

## Accessories for DA Type Distribution Boards

Vertical stacking kits	
Stacking kit for 270mm width	DAXSK08
Stacking kit for 323mm width	DAXSK11
Stacking kit for 377mm width	DAXSK14
Stacking kit for 430mm width	DAXSK17
Stacking kit for 484mm width	DAXSK20
Stacking kit for 555mm width	DAXSK24
<b>Blanking kits</b>	
Busbar terminal blanks (set of 10)	DAXTP
<b>Earth bar kits</b>	
Earth bar	DAXEB
Earth bar isolation kit	DBXL
<b>Door lock kits</b>	
Cylinder door lock	DBXCL
Padlock bracket kit	DBXPL