## **ENERGY DATA**

CODE 11128

## MF 120/5" T

Wall axial fans





ATTRIBUTO	VALORE ATTRIBUTO
Supplier's name or trade mark	Vortice
Specific Energy Consumption class SEC in average climate zone	NA
Specific Energy Consumption class SEC average [kWh/m2a]	-8,8
Specific Energy Consumption class SEC cold [kWh/m2a]	-22,1
Specific Energy Consumption class SEC warm [kWh/m2a]	-1,1
Declared typology	UVR-U: unidirezionale
Type of drive	NA
Type of heat recovery system HRS	assente
Thermal efficiency of heat recovery at reference air flow [%]	NA
Maximum flow rate [m3/h]	173
Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W]	21,4
Sound power level LWA [dB(A)]	60
Reference flow rate [m3/s]	0,0336
Reference pressure difference [Pa]	24
SPI [W/(m3/h)]	0,15111
Control factor CTRL	1
Control typology	manuale
Maximum internal leakage rates [%]	NA
Maximum external leakage rates [%]	NA
Mixing rate	NA
Position and description of visual filter warning	NA
Airflow sensitivity to pressure variations at + 20Pa and – 20 Pa	NA
Indoor/outdoor air tightness [m3/h]	NA
Annual electricity consumption (AEC) [kWh electricity/a]	208
AHS average Annual heating saved [kWh primary energy/a]	1397
AHS cold Annual heating saved [kWh primary energy/a]	2732
AHS warm Annual heating saved [kWh primary energy/a]	632