




ARC



IP65 compact bulkhead luminaire

FEATURES (ALL MODELS)

- Soft arc linear lens diffuser designed to provide maximum spacings between emergency luminaires
- IP65 flame retardant polycarbonate enclosure (white base/clear diffuser) and screw-fixing diffuser located with brass threaded inserts
- Can be fitted with a self-adhesive legend kit (SAL1) to create an exit sign
- Several versions are BSI Kitemarked
- Ideal for use in corridors, exits and escape routes

FEATURES (LED MODELS ONLY)

- LED high output options suitable for high bay applications
- TM-21 L70 greater than 36,000 hours using 0.5W 150 lumen/Watt LEDs
- CRI 80 (minimum)
- 3 step MacAdam rated
- 4000K colour temperature as standard (2700K - 6500K available to order)

CATALOGUE NUMBERS & INFORMATION

Mains Luminaires

Cat No	Light Source & Mode	Mains Lumens	Emergency Lumens	Weight (kg)
AR/LED	5 x 0.5W LED mains (standard output)	145	-	0.90
AR/LED/H	15 x 0.5W LED mains (high output)	360	-	0.90
AR2X8/HF	2 x 8W T5 HF mains	640	-	0.90
AR11/HF	11W TC-S HF mains	720	-	0.90

Emergency Luminaires

Cat No	Light Source & Mode	Mains Lumens	Emergency Lumens	Weight (kg)
AR/LED/M3*	5 x 0.5W LED M3	145	145	1.20
AR/LED/C3	0.5W LED C3 standard output (15 x 0.5W LEDs mains healthy) / 5 x 0.5W LEDs emergency)	145	145	1.20
AR/LED/C3/H	0.5W LED C3 high output (15 x 0.5W LEDs mains healthy & emergency)	360	320	1.20
AR/LED/NM3H	15 x 0.5W LED NM3	-	320	1.20
AR8/NM3*	8W T5 NM3 standard output	-	120	1.20
AR8/NM3/E*	8W T5 NM3 economy output	-	80	1.20
AR8/NM3/H	8W T5 NM3 high output	-	180	1.20
AR8/M3	8W T5 M3 standard output	320	120	1.45
AR8/M3/E	8W T5 M3 economy output	320	80	1.45
AR8/M3/H	8W T5 M3 high output	320	180	1.45
AR2X8/NM3	2 x 8W T5 NM3 standard output	-	150	1.70
AR2X8/NM3/H	2 x 8W T5 NM3 high output	-	250	1.70

* Indicates BSI Kitemarked product

Slave Luminaires

Cat No	Light Source & Mode	Mains Lumens	Emergency Lumens	Weight (kg)
AR/LED/#D	5 x 0.5W LED slave	145	120	0.85
AR8/#D	8W T5 slave	320	275	1.20

Replace # with AC/DC system Voltage 24, 50, 110 or 230 Volts

SPECIFICATION

Suitable for indoor use
 Suitable for outdoor use
 Can be converted into an exit sign using SAL1 self-adhesive legend kit
 Surface mounting
 Semi-recessed version available
 Mains versions available
 Emergency versions available
 Slave versions available
 LED versions available
 T5 and compact fluorescent versions available
 IP65 ingress rating
 CE marked
 BSI Kitemark

DIMENSIONS

Luminaire: Length 350mm x Width 108mm x Depth 80mm
Cut-Out: Length 330mm x Width 90mm (when used with AR/WH semi-recessing kit)
Viewing Distance: 18 metres (when supplied SAL1 legend kit)

OPTIONS

/AD Intelligent addressable luminaire (not available in 8W M3 versions)
/AR/WH White semi-recessing kit
/DAE DALI emergency mode only
/HF High frequency ballast
/SAL1 Self-adhesive legend kit
/ST Digital self-test luminaire (not available in 8W M3 versions)
/TS Push-to-test switch
/NR Anti-tamper screws