



TWISTER CONNECTORS

TWISTER WIRE CONNECTOR SOLUTIONS

idealind.com

Twister® ProFLEX Wire Connector

Twister® ProFLEX™ combines the most comfortable connector from IDEAL with the added protection of a flexible skirt.

It delivers the widest wire combination range with the highest voltage rating in the industry, every day performance professional electricians can trust.

- Flexible skirt provides improved protection and adapts to tightly fit electrical boxes with limited space
- Swept wing design with SureGrip™ overmould offers greater comfort, leverage, and torque for faster connections
- Expanding square-wire spring and polypropylene shell deliver a secure connection every time
- Widest range in the industry
- Tough, UL 94V-2 flame-retardant shell rated at 105°C (221°F)
- IEC 60998-2, EN 60998-2-4 and UL 486 C compliant



Model	Wire Combination Range (mm)	Wire Combination Range AWG	Quantity	Cat. No.
347	1000V 0.34mm ² to 10.0mm ² Min. 2 x 0.75mm ² Max. 4 x 4.0mm ² / Max. 3 x 6.0mm ²	1000V 22-8 AWG Min. 2 #18 - Max 4 #10	Box of 50	30-1047



Twister® ProFLEX Mini Wire Connector

The Twister® ProFLEX™ Mini combines the most comfortable wire connector from IDEAL Electrical with the added protection of a flexible skirt.

Its space-saving design fits the tightest electrical spaces while accommodating the widest wire range of any orange/blue connector from 2 #22 AWG to 4 #12 solid AWG wire

- Expanding square-wire spring and polypropylene shell deliver a secure connection every time
- Swept wing design with SureGrip™ overmould offers greater comfort, leverage, and torque for faster connections
- Flexible skirt provides improved protection and adapts to tightly fit electrical boxes with limited space
- Widest range in the industry
- Tough, UL 94V-2 flame-retardant shell



Model	Wire Combination Range (mm)	Wire Combination Range AWG	Quantity	Cat. No.
343	600V* 0.34mm ² to 4.0mm ² Min. 2 x 0.34mm ² Max. 4 x 4.0mm ²	600V 22 to 12 AWG Min. 2 #22 – Max. 4 #12 Solid	Box of 100	30-343
			Jar of 500	30-6433
			Barrell of 35,000	30-843



UL File E5238

Twister® Pro Wire Connector

Cushion-Grip Swept Wing

- SureGrip™ overmoulding provides improved leverage, more torque, and faster connections
- Accepts solid, stranded and flexible wires and are reusable
- Swept wings offer extra leverage and less effort for large wire combinations
- Live-action, square-wire spring locks onto wire for safe, secure connections
- Deep skirt helps protect against flash-over and turned-back strands for maximum dielectric protection
- Cost effective replacement for terminal blocks
- Widest range in the industry
- Tough, UL 94V-2 flame-retardant shell rated at 105°C (221°F)
- BS 7671:2008 (18th Edition), IEC 60998-1, IEC 60998-2-4 and UL 486 C compliant
- CE, UKCA and UL listed



Model	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
344®	600V* 22 to 8 AWG Min. 2 #18 - Max. 4 # 10	32A/600V*/ 105°C (221°F) 0.5mm ² to 4.0mm ² Min. 3 x 0.5mm ² Max. 4 x 4.0mm	Box of 50	30-144
			Jar of 250	30-244J
			Jar of 500	30-644J
			Barrel of 20,000	30-944

* 1,000V maximum in fixtures and signs



Twister® Wire Connectors


The No.1 twist-on wire connector. The Twister® easily handles the most common wiring tasks. A patented, expanding square-wire spring always ensures a quick, safe connection.

- Exceptional wire-range capacity – three colour-coded models handle wire combinations from as small as 0.5 mm² (22 AWG) to as large as 10.0 mm² (8 AWG)
- Accept solid, stranded and flexible wires and are reusable
- Swept wings offer extra leverage and less effort for large wire combinations
- Live-action, square-wire spring locks onto wire for safe, secure connections
- Deep skirt helps protect against flash-over and turned-back strands for maximum dielectric protection
- Cost effective replacement for terminal blocks
- BS 7671:2008 (18th Edition), IEC 60998-2, IEC 60998-2-4 and UL 486 C compliant
- CE, UKCA and UL listed



Model	Colour	Wire Combination Range (AWG)	Wire Combination Range (mm)	Qty.	Cat. No.
340®	Orange	600V* 22 to 10 AWG Min. 2 #22 - Max. 3 #12	32A / 450V 0.5mm ² to 4.0mm ² Min. 2 x 0.5mm ² Max. 2 x 4.0mm ²	Box of 100	30-340
341®	Tan	600V* 22 to 8 AWG Min. 3 #22 - Max. 3 #10	41A / 600V 0.5mm ² to 6.0mm ² Min. 3 x 0.5mm ² Max. 2 x 6.0mm ²	Box of 100	30-341
342®	Grey	600V* 18 to 6 AWG Min. 3 #14 - Max. 2 #8 w/2 #12	57A / 600V 2.5mm ² to 10.0mm ² Min. 3 x 2.5mm ² Max. 2 x 10.0mm ²	Box of 50	30-342

*1,000V maximum in fixtures and signs



WIRE-NUT® WIRE CONNECTORS

The American classic since 1928.

- Fixed square spring for a secure hold
- Refined range to handle all common applications
- Positive grip shell that is perfect to twist-on with fingers
- Excellent for fine stranded wire applications
- UL Listed to 105°C (221°F)
- IEC 60998-1, IEC 60998-2-4 and UL 486 C compliant
- CE, UKCA and UL listed



Model	Colour	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
71B®	Grey	300V 22 to 16 AWG Min. 2 #22 Str. Max. 2 #16	300V 0.34mm ² to 1.5mm ² Min. 2 x 0.34mm ² Max. 3 x 1.5mm ²	Box of 100	30-071
				Carton of 1,000	30-171
72B®	Blue	300V 22 to 14 AWG Min. 2 #22 Max. 3 #16	300V 0.34mm ² to 2.5mm ² Min. 2 x 0.34mm ² Max. 3 x 1.5mm ²	Box of 100	30-072
				Carton of 1,000	30-172
				Keg of 10,000	30-272
73B®	Orange	600V* 22 to 14 AWG Min. 1 #18 w/l #20 Max. 2 #14	600V* 0.34mm ² to 2.5mm ² Min. 1 x 0.75mm ² w/l x 0.5mm ² Max. 4 x 1.5mm ² w/l x 0.50mm ²	Box of 100	30-073
				Jar of 300	30-073J
74B®	Yellow	600V* 18 to 12 AWG Min. 2 #18 Max. 4 #14 w/l #18	600V* 0.75mm ² to 4.0mm ² Min. 2 x 0.75mm ² Max. 4 x 2.5mm ² w/l x 0.75mm ²	Carton of 1,000	30-173
				Box of 100	30-074
76B®	Red	600V* 18 to 6 AWG Min. 2 #14 Max. 4 #12	600V* 0.75mm ² to 16.0mm ² Min. 2 x 2.5mm ² Max. 2 x 4.0mm ²	Jar of 175	30-074J
				Box of 100	30-076
76B®	Red	600V* 18 to 6 AWG Min. 2 #14 Max. 4 #12	600V* 0.75mm ² to 16.0mm ² Min. 2 x 2.5mm ² Max. 2 x 4.0mm ²	Jar of 150	30-076J
				Box of 100	30-076

*1,000V maximum in fixtures and signs



HIGH-TEMP WIRE-NUT® WIRE CONNECTORS

All of the same features as the Wire-Nut® Wire Connector, plus:

- Black, thermoplastic shell designed to withstand extreme heat build-up found in high-wattage light fixtures and signs
- UL Listed to 150°C (302°F)
- UL 486 C compliant



Model	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
71B®	300V 22 to 16 AWG Min. 2 #22 Str – Max. 2 #16	300V 0.34mm ² to 1.5mm ² Min. 2 x 0.34mm ² – Max. 2 x 1.5mm ²	Box of 100	30-3627
			Carton of 1,000	30-151
			Keg of 25,000	30-251
72B®	300V 22 to 14 AWG Min. 2 #22 – Max. 3 #16	300V 0.34mm ² to 2.5mm ² Min. 2 x 0.34mm ² – Max. 3 x 1.5mm ²	Box of 100	30-3628
			Keg of 10,000	30-252
73B®	600V* 22 to 14 AWG Min. 1 #18 w/l #20 Max. 2 #14	600V* 0.34mm ² to 2.5mm ² Min. 1 x 0.75mm ² w/l x 0.50mm ² Max. 4 x 1.5mm ² w/l x 0.50mm ²	Box of 100	30-3629
			Keg of 10,000	30-253
			Barrel of 50,000	30-803
59B™	600V* 22 to 12 AWG Min. 2 #20 – Max. 3 #14	600V* 0.34mm ² to 4.0mm ² Min. 2 x 0.5mm ² – Max. 3 x 2.5mm ²	Box of 100	30-059
			Keg of 5,000	30-259

*1,000V maximum in fixtures and signs



WING-NUT® WIRE CONNECTORS

High-Leverage Wing

- Contoured wing profile provides extra leverage for superior torque
- Expanding, live-action spring expands to accommodate a wide range of wire sizes and combinations
- Co-polymer shell expands for smooth, progressive tightening providing dependable connections
- Removable for repeat usage on same size or larger combinations
- Tough, UL94V-2 flame retardant shell rated at 105°C (221°F)
- IEC 60998-1, IEC 60998-2-4 and UL 486 C compliant
- CE, UKCA and UL listed



Model	Colour	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
451®	Yellow	600V* 18 to 10 AWG Min. 2 #18 Max. 3 #12	600V* 0.75mm² to 6.0mm² Min. 2 x 0.75mm² Max. 3 x 4.0mm²	Box of 100	30-451
				Jar of 225	30-451J
				Jar of 500	30-651J
				Bag of 500	30-651
452®	Red	600V* 18 to 8 AWG Min. 2 #18 Max. 4 #10 (Widest range in the Industry!)	600V* 0.75mm² to 10.0mm² Min. 2 x 0.75mm² Max. 4 x 6.0mm²	Box of 100	30-452
				Jar of 300	30-452J
				Jar of 500	30-652J
				Bag of 500	30-652
454®	Blue	600V* 14 to 6 AWG Min. 3 #12 Max. 1 #6 w/2 #8	600V* 2.5mm² to 16.0mm² Min. 3 x 4.0mm² Max. 2 x 16.0mm²	Box of 25	30-454
				Bag of 100	30-654

* 1,000 maximum in fixtures and signs



TWISTER® AL/CU WIRE CONNECTORS

Al/Cu Connections


- Only aluminium-to-copper twist-on connector specifically designed to provide a secure connection while preventing aluminium corrosion
- Pre-filled antioxidant compound prevents oxidation of aluminium conductors
- Patent swept wings and hexagonal head for easy installation by hand or with standard nut driver
- Live-action, square-wire spring expands and contracts with aluminium wire
- Entry-cap retains corrosion-resistant compound
- Tough, UL 94V-2 flame-retardant shell rated at 105°C (221°F)
- Complies with N.E.C. Section #110-14(b) for aluminium-to-copper connections; UL Listed to 486C and CSA Certified to C22.2 #188

Model	Colour	Quantity	Part No.
65	Purple	Card of 2	30-065
		Card of 10	30-765
		Card of 25	30-165
		Box of 100	30-265
		Carton of 1,000	30-365

600V maximum building wire; 1,000V signs or light fixtures



Wire Combination Ranges		
1 #10 Al solid w/1 or 2 #10 Cu solid	1 #12 Al w/1 or 2 #14 Cu	
1 #10 Al w/1 or 2 #12 Cu	2 #12 Al solid w/1 #14 Cu	
2 #10 Al solid w/1 #12 Cu	1 #10 Al w/1 or 2 #18 Cu	
1 #10 Al w/1 or 2 #14 Cu	2 #10 Al solid w/1 #18 Cu	
2 #10 Al solid w/1 #14 Cu	1 #12 Al w/1 or 2 #16 Cu	
2 #12 Al solid w/1 #10 Cu	2 #12 Al solid w/1 #16 Cu	
1 #12 Al solid w/1 or 2 #10 Cu	1 #10 Al w/1 or 2 #10 Cu	
1 #12 Al stranded w/1 or 2 #10 Cu solid	2 #10 Al solid w/1 #16 Cu	
1 #12 Al w/1 or 2 #12 Cu	1 #12 Al w/1 or 2 #18 Cu	
2 #12 Al solid w/1 #12 Cu	2 #12 Al solid w/1 #18 Cu	



IP RATED WEATHERPROOF WIRE CONNECTORS

Designed specifically for above ground, interior/exterior connections exposed to damp/wet and corrosive environments.

WeatherProof® connectors are pre-filled with a non-hardening, silicone-based sealant that protects against moisture and corrosion.

- Silicone-based sealant protects against moisture and corrosion
- IP55 rated
- Easy to apply, pre-filled twist-on wire connectors
- Accept solid and stranded wire
- Handle wire sizes from 1.5mm² to 4.0mm² copper conductors
- Tough, UL 94V-2 flame-retardant shell rated at 105°C (221°F)
- BS 7671:2008 (18th Edition), IEC 998-2-4 compliant and UL listed to 486 C and G (sealed twist-on wire connector)
- CE, UKCA and UL listed



Model	Colour	Wire Combination Range (AWG)	Wire Combination Range (mm)	Qty.	Cat. No.
61	Black/Orange	600V* 22 to 14 AWG Min. 2 #20 - Max 2 #14	24A/450V 1.5mm ² to 2.5mm ² Min. 1 x 1.5mm ² - Max 2 x 2.5mm ²	Card of 25	30-1161
62	Black/Red	600V* 18 to 8 AWG Min. 3 #18 - Max 2 #10 w/1 #14	32A/450V 1.5mm ² to 4.0mm ² Min 2 x 1.5mm ² - Max. 4 x 4.0mm ²	Card of 20	30-1162
63	Black/Dark Blue	600V* 16 to 6 AWG Min. 3 #14 - Max 5 #10	32A/450V 2.5mm ² to 4.0mm ² Min 3 x 2.5mm ² - Max. 6 x 4.0mm ²	Card of 15	30-1163



MUDBUG® UTILITY WIRE CONNECTORS



- Connects underground gas tracer lines providing superior protection
- Moisture and corrosion resistant, pre-filled with non-hardening, 100% silicone
- UL Listed to direct burial test standard 486D up to 600V maximum voltage



Model	Wire Combination Range	Wire Combination Range (mm)	Quantity	Part No.
60®	600V* 20 to 10 AWG Min. 1 #20 w/1 #18 - Max. 1 #10 w/2 #12	600V* 0.5mm ² to 6.0mm ² Min. 1 x 0.5mm ² w/1.75mm ² - Max. 1 x 6.0mm ² w/2 - 4.0mm ²	Carton of 1,000	30-360Y

*1,000V maximum in fixtures and signs



WIRE CONNECTOR APPLICATION GUIDE

WeatherProof	RESIDENTIAL	Receptacles	Ceiling Fans	Can Lights	Thermostat Controls	HVAC	Smoke/CO Detectors	Garage Door Openers	Door Bells
61® Grey/Orange	•	•	•	•	•	•	•	•	•
62® Grey/Red	•	•	•	•	•	•	•	•	•
63® Grey/Dk. Blue	•	•	•	•	•	•	•	•	•

WeatherProof	COMMERCIAL	Security Systems	Exterior Lighting	Street/Parking Lot Lighting	Car Washes	Processing Plants	Traffic Signals	HVAC
61® Grey/Orange	•	•	•	•	•	•	•	•
62® Grey/Red	•	•	•	•	•	•	•	•
63® Grey/Dk. Blue	•	•	•	•	•	•	•	•



WIRE CONNECTOR APPLICATION GUIDE

Twister®		RESIDENTIAL								
		Light Switches	Receptacles	Ceiling Fans	Can Lights	Thermostat Controls	HVAC	Smoke/CO Detectors	Garage Door Openers	Door Bells
340™ Orange		•	•	•	•	•	•	•		•
341® Tan		•	•			•	•	•		
344® Red/ Yellow		•	•			•		•		
342® Grey										
Wire-Nut®										
71B® Grey					•					
72B® Blue					•	•				•
73B® Orange				•	•		•			•
74B® Yellow		•		•	•		•			
76B® Red		•	•			•		•		
Wing-Nut®										
451® Yellow		•	•	•	•		•			•
452® Red		•	•			•		•		
454® Blue										

Twister®		COMMERCIAL								
		Multi-Gang Switch Boxes	Security Systems	Intercoms	Recessed Lighting	Controls	Illuminated Signage	Receptacles	3-Phase Motors	HVAC
340™ Orange			•	•	•	•				
341® Tan			•		•	•				•
344® Red/ Yellow		•	•			•	•	•	•	•
342® Grey		•				•	•		•	•
Wire-Nut®										
71B® Grey			•	•						
72B® Blue			•	•						
73B® Orange			•	•	•					
74B® Yellow					•	•				
76B® Red		•				•	•	•	•	•
Wing-Nut®										
451® Yellow					•					
452® Red		•				•	•	•	•	•
454® Blue		•				•	•		•	•

BR-TWISTERAS-0821-EN Printed in UK

IDEAL INDUSTRIES EMEA

EMEA head office: Unit 3, Europa Court, Warrington, WA5 7TN, U.K. | Offices in the UAE & Germany