

TECHNICAL DATASHEET

AFL030/CCT/PIR/WH



30W IP65 Hunter Slim Design CCT PIR Floodlight White



PRODUCT FEATURES

- Easy-Install Angled Bracket
- Tri-Colour Selectable (3000K, 4000K & 6000K)
- Slimline Die-cast Aluminium Construction
- Prismatic Toughened Glass
- Push Terminals for Effortless Install
- Built-in Junction Box
- Manual Override
- Active Occupancy Monitoring Sensor
- Fully Adjustable PIR

DIMENSIONS



Product Code	AFL030/CCT/PIR/WH	
Rated Power	30W	
Housing Colour	Polar White	
Operating Voltage	220-240V	
Frequency	50-60Hz	
CRI	>80	
PF	>0.9	
Beam Angle	120°	
Lifetime to LM70	<30,000 hr	
Operating Temperature	-25°C ~ +40°C	
SDCM	<6	
Starting Time	0.5s	
Ingress Protection	IP65	
LED Chip Type	SMD2835	
Guarantee	2 years	
Detection Angle:	120 Degrees	
Detection Range	2-10 Meters	
Hold Time:	10 Sec +/- 5 second to 10 Min +/- 2 Min	
Lux Setting:	3-2000 Lux	
Lumens		
3000K	≤2240Lm	
4000K	≤2780Lm	
6000K	≤2465Lm	
CCT	3000K /4000K /6000K	
Switching Cycles	≤15,000	
Peak Intensity		
3000K	848cd	
4000K	1039cd	
6000K	889cd	
Class	I	

