

### Installation accessories



Characteristics					Mounting plates		
					Mounting plates made to adapt to all usage scenarios.		
Material					Galvanised-steel	Insulating polyester plate reinforced with fibreglass, halogen-free: glow wire resistance 750°C.	
Thickness					15/10° mm	25/10° mm	
Installation					<ul style="list-style-type: none"> <li>■ Fixing by means of Ø 4-mm self-tapping screws, Pozidrive and slotted head, ref. <b>NSYAMFSTB</b></li> <li>■ To raise the plate, use the stand-offs ref. <b>NSYAMFET154TB</b>, <b>NSYAMFET204TB</b>, <b>NSYAMFET304TB</b> and the screw <b>NSYAMFESTB</b></li> <li>■ To stack several mounting plates, use the spacers, ref. <b>NSYAMFEP154TB</b>, <b>NSYAMFEP204TB</b>, <b>NSYAMFEP304TB</b> and the screw <b>NSYAMFESTB</b></li> </ul>		
Supply					Plates supplied without screws		
Box (mm)		Dimensions (mm)		Minor pack.	References		
Height	Width	A	B				
192	164	168.5	140	1	<b>NSYAMP1916TB</b>	<b>NSYAMPA1916TB</b>	
241	194	215	168.5	1	<b>NSYAMP2419TB</b>	<b>NSYAMPA2419TB</b>	
291	241	265	215	1	<b>NSYAMP2924TB</b>	<b>NSYAMPA2924TB</b>	
341	291	315	265	1	<b>NSYAMP3429TB</b>	<b>NSYAMPA3429TB</b>	
Accessories					Pack of 100 screws		
Ø 4 x 10 mm					1	<b>NSYAMFSTB</b>	<b>NSYAMFSTB</b>