



## In-Sure™ Push-In Wire Connectors

<b>European rating:</b> EN60998-1	450V	24A	40°	0.75mm <sup>2</sup> -2.5mm <sup>2</sup> solid
EN60998-2-2				1.5mm <sup>2</sup> -2.5mm <sup>2</sup> rigid stranded

### **Installation Instructions:**

1. Wiring and installation must comply with applicable electrical regulations
2. Do not exceed the rating of these connectors
3. Turn off power before removing or installing connectors
4. Strip wires back 13mm
5. Grip wire firmly and push conductor into open port. Use only one conductor per port
6. One time use only. Do not reuse
7. Do not use on aluminium wire

### **! WARNING !**

Contact with electricity can cause serious injury or death. Shut off power at the circuit breaker or remove fuse before using this product.



### **CUSTOMER SAFETY NOTICE**

Please be advised that these connectors are not designed for use with flexible stranded wire cables. The use of stranded wire is limited to 1.5mm<sup>2</sup> - 2.5mm<sup>2</sup> rigid stranded ( 7 strands) only.

Light gauge stranded wires of the kind typically used in lighting applications (flex with 7 strands) do not have sufficient rigidity to allow proper insertion into the connector body. Incorrect use of these connectors can be dangerous and may cause electrical fires.

To the extent permitted by law, Ideal Industries Inc. excludes its liability for any use of these connectors other than in accordance with the instructions and this customer safety notice.

**IDEAL INDUSTRIES LIMITED.** • Unit 3 • Europa Court • Europa Boulevard • Westbrook • Warrington • Cheshire • WA5 7TN • tel: 01925 44 44 46 • fax: 01925 44 55 01 • [www.idealindustries.co.uk](http://www.idealindustries.co.uk) • [uksales@idealnwd.com](mailto:uksales@idealnwd.com)