

## ONYX FLOOD



130lm/W

65

06

5000k

WARRANTY  
2YRS

The 3rd generation **Onyx** flood is our most efficient flood lamp to date, with a high lumen output, sleek and lightweight design, including our unique HydraGasket seal technology. It is easy to install, very cost effective and reliable.

All **Onyx** floods come with a mounting bracket which allows for up to 270° rotation and is pre-flexed with 1m of watertight cable.

The **Onyx** 3rd generation now has a voltage input range of between 110-240V which makes it suitable for both industrial and site lighting.

### Additional benefits and what's included

- 1m mains cable
- Bracketry 270°
- 110-240V AC input
- Lightweight housing
- Low glare toughened glass diffuser
- HydraGasket technology – for complete water ingress protection

### Available options

Marine/Coastal upgrade kit



Code	Name	Wattage	Lumens	Colour temp.	CRI	IP	Rated	Replacement for
EL50X3F	Onyx 50W Flood	50W	6500lm	5000K	>70	65	25000hrs	75W HID
EL100X3F	Onyx 100W flood	100W	13000lm	5000K	>70	65	25000hrs	250W MH/SON
EL150X3F	Onyx 150W flood	150W	19500lm	5000K	>70	65	25000hrs	400W MH/SON
EL200X3F	Onyx 200W flood	200W	26000lm	5000K	>70	65	25000hrs	500W MH/SON
EL300X3F	Onyx 300W flood	300W	36000lm	5000K	>70	65	25000hrs	600W MH/SON

SELECTABLE OUTPUT  
132lm/W

20

08

4000k

WARRANTY  
5YRS

## SOLRAY SELECT LINEAR BATTEN



### Available options

Self test emergency

Microwave or PIR on/off

DALI/Mains dimmable

Designed to replace traditional fluorescent tubes and their fittings, these versatile, efficient and easy to install **Solray Select** Linear LED fittings are ideal for use in warehouses, offices, schools and medical centres. The ability to select the light level you require using one of 4 individual settings in one unit makes this a truly unique product, which then makes it easier to set the ideal light levels when on site.



### Additional benefits and what's included

- Flicker free
- Push terminal through wiring
- 4 switchable light level outputs
- CRI >80
- Key slot mounts
- BESA mounts
- Long life aluminium and PC body
- Cable gland

Code	Name	Wattage	Lumens	Colour temp.	CRI	IP	Rated	Replacement for
EL2SR2B	Solray LED Batten 2ft 18W	18W	2160lm	4000K	>80	20	50,000hrs	Twin 2ft T5/T8 Tube
EL4SR2B	Solray Select LED Batten 4ft 22-40W	22-40W	2600lm - 4410lm	4000K	>80	20	50,000hrs	Single/Twin 4ft T5/T8 Tube
EL5SR2B	Solray Select LED Batten 5ft 28-50W	28-50W	3700lm - 6100lm	4000K	>80	20	50,000hrs	Single/Twin 5ft T5/T8 Tube
EL5HSR2B	Solray Select LED Batten 5ft High Output 36-62W	36-62W	5500lm - 9000lm	4000K	>80	20	50,000hrs	Twin 5/6ft T5/T8/T10/T12 Tube
EL6SR2B	Solray LED Batten 6ft 65W	65W	9000lm	4000K	>80	20	50,000hrs	Twin 6ft T8/T10/T12 Tube

**When ordering, please specify the product variation you are interested in by adding the following suffixes to the product's code.**

**D:** DALI Dimmable      **F:** Self Test Emergency      **M:** Microwave On/Off

*Example:* A Solray Select LED Batten 4ft 22-40W Self Test Emergency + Microwave would be:

**EL4SR2BFM** which is **EL4SR2B + F + M**

*Note:* any additional codes to be added in alphabetical order.