

Onyx 150W flood

EL150X3F



PRODUCT DATA

LUMENS (lm)	19500lm
WATTAGE (W)	150W
COLOUR TEMPERATURE (K)	5000K
WEIGHT (kg)	3.35kg
BEAM ANGLE	120°
WINDAGE	0.14m ²
CRI	>70
REPLACEMENT FOR	400W MH/SON
DIMENSIONS (mm)	364x315x54mm
PRODUCT TYPE	Floods
EFFICIENCY (lm/w)	130lm/W
RATED LIFETIME (hrs)	25,000hrs
IP	65
WORKING ENVIRONMENT	-20°C to 40°C
WARRANTY	2 year


KEY FEATURES

The high output of the Onyx 150W flood (3rd generation) makes it a perfect replacement for a 400W MH/SON and is ideal as a high powered floodlight. The input voltage range of 100-240Vac allows for use in both commercial, industrial and construction site lighting.


COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. Not suitable for swimming pool areas or for use as a low bay or high bay - please contact us for information on our products which are suitable.

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

