

PRODUCT DATA SHEET

Onyx 200W flood

EL200X3F





PRODUCT DATA

LUMENS (Im)	26000lm
WATTAGE (W)	200W
COLOUR TEMPERATURE (K)	5000K
WEIGHT (kg)	4.6kg
BEAM ANGLE	120°
WINDAGE	0.18m2
CRI	>70
REPLACEMENT FOR	500W MH/SON
DIMENSIONS (mm)	418x368x56mm
PRODUCT TYPE	Floods
EFFICIENCY (Im/w)	130lm/W
RATED LIFETIME (hrs)	25,000hrs
IP	65
HOUSING COLOUR	Black
WORKING ENVIRONMENT	-20°C to 40°C
WARRANTY	2 years


KEY FEATURES

The high output of the Onyx 200W flood (3rd generation) makes it a perfect replacement for a 500W MH/SON and is ideal as a high powered floodlight. The input voltage range of 100-240Vac allows for use in both commercial, industrial and construction site lighting.


COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. Not suitable for swimming pool areas or for use as a low bay or high bay - please contact us for information on our products which are suitable.

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS



