

Solray Select LED Batten 5ft High Output 34-58W

EL5HSR2B



PRODUCT DATA

LUMENS (lm)	9300lm
WATTAGE (W)	34-58W
COLOUR TEMPERATURE (K)	4000K
WEIGHT (kg)	1.5kg
BEAM ANGLE	110° x 130°
CRI	>85
REPLACEMENT FOR	
Single or twin T8 58W 5ft and Single or Twin T5 80W 5ft	
DIMENSIONS (mm)	1530 x 60 x 74mm
PRODUCT TYPE	Linear battens
EFFICIENCY (lm/w)	Up to 170lm/W
RATED LIFETIME (hrs)	50,000hrs
IP	20
HOUSING COLOUR	RAL9003
WORKING ENVIRONMENT	-20°C to 35°C
WARRANTY	5 year
L70 RATING (hrs)	>80000hrs

SELECTABLE SETTINGS

WATTAGE	LUMENS	WATTAGE	LUMENS
34W	5800lm		
43W	7200lm		
52W	8500lm		
58W	9300lm		


KEY FEATURES

Perfect for new installations and like-for-like replacements, this batten allows the client to choose the light level that they require during the installation process. This exciting development means that the Solray Select High Output is equivalent to both 5ft and 6ft Single and Twin T5 Fluorescent Tubes with lumen range of 5500-9000 lumens. The flicker free operation, BESA mounting and M20 cable entry allow the unit to easily replace older fluorescent models.


COMMERCIAL APPLICATIONS

Offices, schools, corridors, medical centres

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

