Product datasheet Characteristics

GD2G2WC

Exclusive dimmer switch 250VA, 2gang, 2way, mains & low voltage



Range	Exclusive	
Product or component type	Push-button dimmer	
Quantity per set	Set of 1	
Device presentation	Complete product	
Load type	Incandescent lamp Dimmable fluocompact lamp: 250 W	
Colour tint	White matt	

Complementary

Range	Exclusive	
Product or component type	Push-button dimmer	
Quantity per set	Set of 1	
Device presentation	Complete product	
Load type	Incandescent lamp Dimmable fluocompact lamp: 250 W	
Colour tint	White matt	
Complementary		
Device mounting	Wall mounted	
Dimmer application	Inductive load Resistive load	
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	2 gangs	
Connections - terminals	Screw terminals	
Fixing mode	By screws M3.5 x 30 mm	
Material	Urea (carbamide)	
Height	86 mm	
Width	86 mm	
Depth	17 mm	
Environment		
Standards	BS EN 60669-2-1	
IP degree of protection	IP20	
Packing Units		
Package 1 Weight	170.000 g	
Offer Sustainability		
REACh Regulation	REACh Declaration	

Environment

		0
Standards	BS EN 60669-2-1	0
IP degree of protection	IP20	- · · · · · · · · · · · · · · · · · · ·

Packing Units

r doming office	
Package 1 Weight	170.000 g

Offer Sustainability

<u> </u>	
REACh Regulation	REACh Declaration

REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Warranty	18 months