



Fuse-link, low voltage, 2 A, AC 500 V, 100 kA, D1, 13.2 x 6 mm, gL/gG, IEC, time-delay



Powering Business Worldwide™

**Part no.** FU5E-D1 2A T GL/GG 500VAC E16  
**Catalog No.** 2D16

**EL-Nummer (Norway)** 1600303

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	2
Rated voltage			AC 500 V
Construction size			D1
Size			13.2 x 6 mm
Utilization category			gL/gG
Breaking Capacity		kA	100
usable for size/applications			E16 for domestic and general industrial applications
Release characteristic	class		time-delay
Standard/Approval			IEC
Shape			bottle
Standards/Regulations			IEC 60269-3 VDE 0636

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss10.0.1-27-14-20-04 [AFZ799015])			
Construction size			D1
Rated current		A	2
Rated voltage		V	500
Colour code			Pink
Utilization category			gL/gG (cable protection/equipment protection)
Release characteristic			Time-lag