

Onyx 300W flood

EL300X3F



PRODUCT DATA

| | |
|------------------------|---------------|
| LUMENS (lm) | 36000lm |
| WATTAGE (W) | 300W |
| COLOUR TEMPERATURE (K) | 5000K |
| WEIGHT (kg) | 4.77kg |
| BEAM ANGLE | 120° |
| WINDAGE | 0.25m2 |
| CRI | >70 |
| REPLACEMENT FOR | 600W MH/SON |
| DIMENSIONS (mm) | 529x415x55mm |
| PRODUCT TYPE | Floods |
| EFFICIENCY (lm/w) | 120lm/W |
| RATED LIFETIME (hrs) | 25,000hrs |
| IP | 65 |
| HOUSING COLOUR | Black |
| WORKING ENVIRONMENT | -20°C to 40°C |
| WARRANTY | 2 year |


KEY FEATURES

The high output of the Onyx 300W flood (3rd generation) makes it a perfect replacement for a 500W MH/SON and is ideal as a high powered floodlight. The input voltage range of 100-240Vac allows for use in both commercial, industrial and construction site lighting.


COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. Not suitable for swimming pool areas or for use as a low bay or high bay - please contact us for information on our products which are suitable.

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

