

6W Firestay LED Integrated Fixed Downlight, Incl White & Satin Bezel - 3000K, 40° Beam Angle - Plug & Play Fitting



The Firestay Integrated Fixed Downlight boasts a 3 year guarantee and is supplied with white & satin bezels as standard.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & metal web ceiling systems
- IP65
- Part B/C/E compliant
- White bezel & magnetic satin bezel
- Part L compliant

Codes

| | |
|----------------|---------------|
| Commodity Code | 94054099 |
| EAN | 5013588105000 |
| Luckins Code | 405872082 |

Technical

| | |
|-----------------|----------|
| Volts (V) | 220-240 |
| Watts (W) | 6 |
| Colour Temp (K) | 3000 |
| Lumens (lm) | 580 |
| Candelas | 1,050 cd |

| | |
|--------------------------------|------------------|
| Life Hours | 35,000 h |
| Guarantee | 3 Year Guarantee |
| Beam Angle | 40° |
| CRI (ra) | 85 |
| Switching Cycles | 10,000 |
| Frequency (Hz) | 50 |
| Energy Consumption (kWh/1000h) | 6 |
| IP Rating | IP65 |

Dimensions

| | |
|--|----------|
| Downlight Cut Out (mm) | 60-70 |
| Width | 53.5 mm |
| Bell_Depth | 69 mm |
| Diameter | 81 mm |
| Individual Product Weight (no packaging) | 0.047 kg |

Packaging

| | |
|----------------------|-------------|
| Single Carton Weight | 0.275 kg |
| Single Carton Height | 8.5 cm |
| Single Carton Width | 8.6 cm |
| Single Carton Depth | 9.8 cm |
| Inner Box Weight | 3 kg |
| Inner Box Height | 45 cm |
| Inner Box Width | 21 cm |
| Inner Box Depth | 10 cm |
| Outer Box Weight | 6.5 kg |
| Outer Box Height | 46.5 cm |
| Outer Box Width | 22.5 cm |
| Outer Box Depth | 22.5 cm |
| Inner Box Qty | 10 |
| Outer Box Qty | 20 |
| Outer Box CMB | 0.023540625 |