Datasheet



YFIP63

Term Tech Pre-Insulated Terminals Yellow Female Push On 4mm²-6mm² Cable Fully Insulated 6.3mm Wide Receptacle 0.5mm Tab Thickness (Bag of 100)



The Termination Technology range of pre-insulated terminals are colour coded to cover $0.5 \, \text{mm}^2$ up to $6 \, \text{mm}^2$ cable sizes and includes a wide variety of types from rings, forks, pins, blades and more. Manufactured from oxygen-free high conductivity copper which is electro-tin plated for excellent resistance to corrosion. PVC insulation with a maximum working temperature of $75 \, ^{\circ}\text{C}$. All supplied in display counter packs of 100.

Technical Data

Colour and Material

Material	Copper
Insulation Material	Polyvinyl Chloride (PVC)
Insulation Style	Fully Insulated
Plating Material	Electro-Tin Plating

Application Type, Size and Range

Cable Size Range (mm²)	4 - 6
Number of Cables Accepted	1
Suitable Cable Type	Copper Cores

Dimensions

Recepticle Width (mm)	6.3
Tab Thickness (mm)	0.5

Product Specification

Specific Approvals	UL Certified
UKCA Approved	Yes



W: www.termtech.co.uk
T: 01179 354 900
E: sales@termtech.co.uk

sales@termtech.co.uk

The company with the RIGHT connections at the RIGHT price.

Company Registration Number: 05062297







Datasheet



Quantities and Packaging

Packaging Euroslot trade counter pack

Temperature and Fire Information

Max Operating Temperature (°C) 75





W: www.termtech.co.uk
T: 01179 354 900
E: sales@termtech.co.uk

The company with the RIGHT connections at the RIGHT price.

Termination Technology Ltd, Unit 4C Crofts End Ind Estate, Crofts End Road, Bristol BS5 7UW





