

SURGE

The Surge range consists of compact and budget friendly floodlights. They provide a high light output and a colour temperature of 4000K. Boasting an angled bracket to ensure easy installation and flexibility to suit your lighting needs. IP44 rated to ensure protection against water. 3 year warranty as standard and comes pre wired with a 1m flex cable. Various sizes & PIR versions are available.



IP65
RATED

ANGLED
BRACKET

PRE-CABLE
1M

Angled bracket



- Constructed from die cast aluminium alloy & glass
- Matt black finish
- LED module (SMD)

CODE	DESCRIPTION	K	LM	LM/W	DIMENSIONS	
78962	Surge 10W IP65 10W	A	4000	800	80	Proj: 27mm H: 125mm W: 104mm
78964	Surge 20W IP65 20W	A	4000	1600	80	Proj: 28mm H: 152mm W: 125mm
78966	Surge 30W IP65 30W	A	4000	2400	80	Proj: 27mm H: 209mm W: 168mm
78968	Surge 50W IP65 50W	A	4000	4000	80	Proj: 36mm H: 237mm W: 200mm
78970	Earth spike					H: 170mm Dia: 45mm

SURGE PIR

The Surge range consists of compact and budget friendly floodlights. They provide a high light output and a colour temperature of 4000K. Boasting an angled bracket to ensure easy installation and flexibility to suit your lighting needs. IP44 rated to ensure protection against water. 3 year warranty as standard and comes pre wired with a 1m flex cable. Various sizes & PIR versions are available.



MANUAL
OVERRIDE
PIR

ANGLED
BRACKET

PRE-CABLE
1M



- Constructed from die cast aluminium alloy & glass
- Matt black finish
- LED module (SMD)
- Complete with manual override PIR
- 2 - 2000 lux
- 120° detection angle
- 8±2m maximum range with 10±5 sec 8±2min timer function

CODE	DESCRIPTION	K	LM	LM/W	DIMENSIONS	
78963	Surge 10W PIR IP44 10W	A	4000	800	80	Proj: 55mm H: 165mm W: 104mm
78965	Surge 20W PIR IP44 20W	A	4000	1600	80	Proj: 55mm H: 189mm W: 125mm
78967	Surge 30W PIR IP44 30W	A	4000	2400	80	Proj: 54mm H: 252mm W: 168mm
78969	Surge 50W PIR IP44 50W	A	4000	4000	80	Proj: 57mm H: 287mm W: 200mm