

SEVERUS BLACK

The Severus is a range of surface mounted LED guide lights, which are quick and easy to fit. Manufactured from polycarbonate, they are the ideal choice for coastal locations. Available in a choice of direct and indirect light, design and finish. The clever design means that you can now fit guide lights when you are not able to cut holes in your wall. The slim profile and integrated driver allows us to keep the projection from the wall to a minimum and the IP rating is ensured by the gasket and the diffuser when it is fitted into place. The outer cover simply clips into place to complete the installation.

62818 61211

61219 61214 61220

IP65 RATED

LED SMD

3 YEAR WARRANTY

SMD

IP65

▶80 CRI

SDCM 6

120°

- Constructed from black ABS plastic & frosted polycarbonate
- LED module (SMD)

CODE	DESCRIPTION	K	LM	LM/W	DIMENSIONS	
61211	Severus landscape direct IP65 3W	A	3000	180	60	Proj: 30mm H: 80mm W: 230mm
61214	Severus landscape indirect IP65 2W	A	3000	65	33	Proj: 30mm H: 80mm W: 230mm
61218	Severus square direct IP65 3W	A	3000	190	63	Proj: 30mm Sq: 125mm
61219	Severus square indirect IP65 1.1W	A	3000	42	38	Proj: 30mm Sq: 125mm
61220	Severus round direct IP65 2W	A	3000	180	90	Proj: 30mm Dia: 150mm

SEVERUS GREY

The Severus is a range of surface mounted LED guide lights, which are quick and easy to fit. Manufactured from polycarbonate, they are the ideal choice for coastal locations. Available in a choice of direct and indirect light, design and finish. The clever design means that you can now fit guide lights when you are not able to cut holes in your wall. The slim profile and integrated driver allows us to keep the projection from the wall to a minimum and the IP rating is ensured by the gasket and the diffuser when it is fitted into place. The outer cover simply clips into place to complete the installation.

EL-40106 EL-40103

EL-40107 EL-40104 EL-40108

IP65 RATED

LED SMD

3 YEAR WARRANTY

SMD

IP65

▶80 CRI

SDCM 6

120°

- Constructed from black ABS plastic & frosted polycarbonate
- LED module (SMD)

CODE	DESCRIPTION	K	LM	LM/W	DIMENSIONS	
EL-40103	Severus landscape direct IP65 3W	A	3000	180	60	Proj: 29mm H: 80mm W: 230mm
EL-40104	Severus landscape indirect IP65 2W	A	3000	65	33	Proj: 27mm H: 80mm W: 230mm
EL-40106	Severus square direct IP65 3W	A	3000	190	63	Proj: 27mm Sq: 125mm
EL-40107	Severus square indirect IP65 1.1W	A	3000	42	38	Proj: 27mm Sq: 125mm
EL-40108	Severus round direct IP65 2W	A	3000	180	90	Proj: 27mm Dia: 150mm