

ShieldECO 500

The ShieldECO is a revolutionary Fire Rated dimmable LED downlight in both performance and installation. Utilising the tool-less fast fix 4 way loop in loop out connection system, the whole product can be fully wired and installed in a matter of seconds. Available in 4W 500 lumen and 8.5W 820 lumen and in both fixed and tilt versions. Owing to its unique construction and heat dissipation the product can be covered directly with insulation when installed in the ceiling. Suitable for both domestic and commercial applications this IP65 range of downlights are available in White, Satin nickel and Polished chrome.

SHIELD ECO



- Constructed from steel & acrylic
- 4W LED module (SMD)
- Min. void 90mm
- Compatible dimmer 75021 (150W), see page 298



Trimless bezel on page 33




Can be covered with insulation

CODE	DESCRIPTION	FINISH	K	LM	LM/W	DIMENSIONS	CUT OUT
73785	ShieldECO 500 4W	Matt white	3000	500	125	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
73786	ShieldECO 500 4W	Matt white	4000	500	125	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
73787	ShieldECO 500 4W	Satin nickel	3000	500	125	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
73788	ShieldECO 500 4W	Satin nickel	4000	500	125	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74031	ShieldECO 500 4W	Chrome plate	3000	500	125	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74032	ShieldECO 500 4W	Chrome plate	4000	500	125	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm

ShieldECO 800

The ShieldECO is a revolutionary Fire Rated dimmable LED downlight in both performance and installation. Utilising the tool-less fast fix 4 way loop in loop out connection system, the whole product can be fully wired and installed in a matter of seconds. Available in 4W 500 lumen and 8.5W 820 lumen and in both fixed and tilt versions. Owing to its unique construction and heat dissipation the product can be covered directly with insulation when installed in the ceiling. Suitable for both domestic and commercial applications this IP65 range of downlights are available in White, Satin nickel and Polished chrome.

SHIELD ECO



- Constructed from steel & acrylic
- 8.5W LED module (SMD)
- Min. void 90mm
- Compatible dimmer 75021 (150W), see page 298



Trimless bezel on page 33



Can be covered with insulation

CODE	DESCRIPTION	FINISH	K	LM	LM/W	DIMENSIONS	CUT OUT
74707	ShieldECO 800 8.5W	Matt white	3000	750	88	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74708	ShieldECO 800 8.5W	Matt white	4000	820	96	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74709	ShieldECO 800 8.5W	Satin nickel	3000	750	88	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74710	ShieldECO 800 8.5W	Satin nickel	4000	820	96	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74711	ShieldECO 800 8.5W	Chrome plate	3000	750	88	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm
74712	ShieldECO 800 8.5W	Chrome plate	4000	820	96	Proj: 3mm H: 59mm Dia: 81.5mm	Dia 57mm