

3 Pole + Sw. Neutral Steel Enclosed Switch-Disconnectors (IP65)



Early Make / Late Break
Neutral Pole (Page 11)



Neutral contacts must be used when switching the neutral.

IEC & EN 60947-3

Dimensions: H:400 x W: 300 x D: 200mm
Suitable for 50mm² SWA Cable / Padlockable in the OFF position for added security (For up to 3 padlocks) / Epoxy powder coated steel RAL 7035 / Bottom gland plate only

All switch ratings at AC-22 - See page 141 for technical data

Part Number	Description	Price	Per
LB1003PSNME	100A 3 Pole + Sw. Neutral (Steel Enclosure)	£172.57	1
LB1253PSNME	125A 3 Pole + Sw. Neutral (Steel Enclosure)	£182.23	1

4 Pole Enclosed Switch-Disconnectors (IP65)



IEC & EN 60947-3

20mm cable entries up to 40A / 25mm on 63 to 125A / Robust polycarbonate enclosure / UV resistant / Enclosure glow wire flammability rating 960°C / Halogen free / Lower smoke generation / Padlockable in the OFF position (for up to 3 padlocks)

Switch Ratings:

AC-21 20-80A - See page 140 for technical data

AC-22 100 & 125A - See page 141 for technical data

Part Number	Description	Price	Per
LB204P	20A 4 Pole (Insulated Enclosure)	£15.30	1
LB254P	25A 4 Pole (Insulated Enclosure)	£19.61	1
LB324P	32A 4 Pole (Insulated Enclosure)	£19.98	1
LB404P	40A 4 Pole (Insulated Enclosure)	£26.92	1
LB634P	63A 4 Pole (Insulated Enclosure)	£29.26	1
LB804P	80A 4 Pole (Insulated Enclosure)	£35.49	1
LB1004P	100A 4 Pole (Insulated Enclosure)	£81.49	1
LB1254P	125A 4 Pole (Insulated Enclosure)	£97.79	1

4 Pole Boxed Isolator Switch (IP65) Dimensions (mm)

Part Number	Height (mm)	Width (mm)	Depth (mm)	Depth (Incl. Switch)	Additional Aux. (Ordered Separately)
LB204P	125	100	74	118	-
LB254P					
LB324P					
LB404P					
LB634P	175	125	90	134	1 Auxiliary
LB804P					
LB1004P					
LB1254P	280	190	130	190	-

4 Pole Larger Enclosure Version (IP65)



More space for easy wiring

IEC & EN 60947-3

25mm cable entries / Robust resilient polycarbonate enclosure / UV resistant / Enclosure glow wire flammability rating 960°C
Padlockable in the OFF position for added security (For up to 3 padlocks)
All switch ratings at AC-21 - See page 140 for technical data

Part Number	Description	Price	Per
LB254PBB	25A 4 Pole (Insulated Enclosure)	£24.42	1
LB324PBB	32A 4 pole (Insulated Enclosure)	£29.09	1
LB404PBB	40A 4 Pole (Insulated Enclosure)	£33.19	1

4 Pole Larger Enclosure Dimensions (mm)

Height (mm)	Width (mm)	Depth (mm)	Depth (Incl. Switch)	Additional Aux. (Ordered Separately)
175	125	90	134	1 Auxiliary

4 Pole Metal Clad Enclosed Switch-Disconnectors (IP54)



IEC & EN 60947-3

20mm cable entries up to 80A / 25mm on 100 to 125A / Padlockable in the OFF position for added security (For up to 3 padlocks) / Cover: RAL 7035 / Base: RAL 7043

Switch Ratings:

AC-21 20-80A - See page 140 for technical data

AC-22 100 & 125A - See page 141 for technical data

Part Number	Description	Price	Per
LB324PSTB	32A 4 Pole (Metal Clad Enclosure)	£43.34	1
LB634PSTB	63A 4 Pole (Metal Clad Enclosure)	£53.61	1
LB804PSTB	80A 4 Pole (Metal Clad Enclosure)	£61.06	1
LB1004PSTB	100A 4 Pole (Metal Clad Enclosure)	£100.74	1
LB1254PSTB	125A 4 Pole (Metal Clad Enclosure)	£108.65	1

4 Pole Metal Clad Enclosure Dimensions (mm)

Part Number	Height	Width	Depth	Depth (Incl. Switch)	Additional Aux. (Ordered Separately)
LB324PSTB	220	145	90	134	1 Auxiliary
LB634PSTB					
LB804PSTB					
LB1004PSTB	270	215	125	185	
LB1254PSTB					