

Fused Switches

Enclosed Door Interlocked Fused Switches 32-100A (IP65)



**Range
Extended**

EN 60947-3 / TUV approved fuse holder to EN60269-1 & HD60269-2
 3 Pole + early make / late break neutral switch
 Switch handle padlockable in the OFF position (For up to 3 padlocks)
 IP20 protection on incoming terminals
 Supplied with fully rated gL fuses (Which can be down rated) (See pages 123-126) / Top and bottom gland plates / All switch ratings AC-22

Part Number	Description	Price	Per
FS323PSNP	32A (Insulated Enclosure)	£85.00	1
FS323PSNME	32A (Metal Enclosure)	£126.60	1
FS633PSNME	63A (Metal Enclosure)	£205.77	1
FS803PSNME	80A (Metal Enclosure)	£213.05	1
FS1003PSNME	100A (Metal Enclosure)	£244.82	1


3P + Sw. Neutral Fused Switch Dimensions (mm)

Part Number	Height (mm)	Width (mm)	Depth (mm)	Depth (Inc Switch)	Fuse Holder	Terminal Capacity
FS323PSNP	280	190	130	178	10 x 38 (see page 123)	10mm ²
FS323PSNME	300	250	150	194		
FS633PSNME	500	300	200	244	22 x 58 (see page 126)	35mm ²
FS803PSNME						
FS1003PSNME						

NB: Fuses should not exceed the maximum rating of the switch

Switch Fuses

125A 2 Pole Door Interlock Switch Fuse



EN60947-3
 Tunnel terminals 95mm² capacity / Padlockable in the OFF position for added security (For up to 3 padlocks) / Door interlock with defeat mechanism (For authorised personnel only) / 22x58 gL/gG fuse (sold separately) / Fuse fully isolated top and bottom for safe replacement / Fuse can be down rated (See page 126)

Part Number	Description	Price	Per
LBFD1252P2258	125A 2 Pole Switch Fuse	£210.78	1

125A 2 Pole Enclosed Switch Fuse (IP65)



EN60947-3
 Tunnel terminals 95mm² capacity
 Padlockable in the OFF position for added security (For up to 3 padlocks)
 Door interlock with defeat mechanism (For authorised personnel only)
 125A 22x58 gL/gG fuse fitted / Fuse fully isolated top and bottom for safe replacement / Fuse can be down rated (See page 126)
 Top and bottom gland plates / Enclosure - H: 500 x W: 300 x D: 200mm

Part Number	Description	Price	Per
LBF1252PME2258	125A Enclosed Switch Fuse	£426.68	1

Photovoltaic DC 4 Pole Switch-Disconnectors

DC 4 Pole Enclosed Switch-Disconnecter (IP66)



EN 60947-3
 Padlockable in the OFF position for added security (For up to 3 padlocks)
 4 x M20 cable entries / Enclosure glow wire flammability rating 960°C
 Robust polycarbonate enclosure / UV resistant / Dimensions: H: 160mm x W: 100 x D: 116mm / Switch rated at 1500V

Part Number	Description	Price	Per
LBDC164P	16A 1500V 4 Pole	£37.50	1
LBDC254P	25A 1500V 4 Pole	£45.00	1
LBDC324P	32A 1500V 4 Pole	£50.00	1

MC4 Connectors IP65



Supplied in sets of two (Male and female connectors) / Panel mount for enclosures / Cable mount for cable in-line applications / Cable capacity: 2.5-6mm² / Rated current: 30A / Rated voltage: 1000V DC

Part Number	Description	Price	Per
MC4C	MC4 Cable Mount PV Male & Female Connectors (Pair)	£2.32	1
MC4P	MC4 Panel Mount PV Male & Female Connectors (Pair)	£2.40	1