



Switch Disconnectors Double Pole

TWO MODULE

PART NO.	DESCRIPTION
H5500s	100A 230V
H5560s	63A 230V

Suitable for installation in MK Sentry consumer units and two or four module enclosures. Accepts direct to busbar or cable-in / cable-out connection.

CATEGORY OF DUTY:

AC22A for switching of resistive and inductive loads. Positive contact status indication in accordance with 17th Edition IEE Wiring Regulations (537.2.2.2 and 537.3.2.2)

DIMENSIONS:

81 x 36 x 76mm

CABLE CAPACITY:

50mm²
BS EN 60947-3:1999



MCBs Single Pole

**TYPE B
ONE MODULE**

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
H5903s	3A 230V	H5925s	25A 230V
H5906s	6A 230V	H5932s	32A 230V
H5910s	10A 230V	H5940s	40A 230V
H5916s	16A 230V	H5945s	45A 230V
H5920s	20A 230V	H5950s	50A 230V
H5925s	25A 230V	H5963s	63A 230V



**TYPE C
ONE MODULE**

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
H8703s	3A 230V	H8725s	25A 230V
H8706s	6A 230V	H8732s	32A 230V
H8710s	10 230V	H8740s	40A 230V
H8716s	16A 230V	H8750s	50A 230V
H8720s	20A 230V	H8763s	63A 230V

Suitable for installation in MK Sentry Consumer Units and two or four module enclosures. Positive contact status indication in accordance with 17th Edition IEE Wiring Regulations (537.2.2.2 and 537.3.2.2)

DIMENSIONS: 83 x 18 x 74mm
CABLE CAPACITY: 35mm²
SHORT-CIRCUIT BREAKING CAPACITY: 6KA
 BS EN 60898:2003

