

JC070172

RadiaLED Rapid Modules

RadiaLED Rapid LED Module 4000K 16W Microwave On/Off Emergency

Features & Benefits

- 16W LED Module, for use with RadiaLED Rapid body JC070156
- 2.5x Faster to install than traditional LED bulkheads
- Detachable terminal, for simple wiring connection
- Multiply cable entry, central and offset rear entry points
- 20mm conduit entry, on top, bottom, sides and rim
- Clip-in tool-less LED gear tray design
- Smooth, even light distribution
- · Bodies, IK10, maximum impact rating
- Bodies, IP65 protection against dust and moisture
- Emergency, microwave and dimmable options
- 6 rim colour options, including black Eyelid



General Information

Product Group

Product Range

Trade Name

Light Source

Light Source Features

Product Shape

Additional Information

Mounting

IP Rating

Distance From Lighted Object

Origin of manufacturer

Warranty

LED Manufacturer/Type

LED-Surface

RadiaLED Rapid

RadiaLED

LED

Neutral White

Round

All lumen values stated are when module is installed in body

Press fit clip into JC070156 Body

IP65 when installed in Body

0.3

China

2 years standard warranty extends to 5 years when registered

within the first year of purchase(2 years on batteries) (See

Website for terms and conditions) Module must be registered with

the body

3528/Nationstar

Electrical

Voltage Rating 220-240

Secondary Running Current 300mA

Primary Running Current 0.18A

Operating Frequency Hz 50/60

CC or CV Constant current

Luminaire Circuit Wattage 16

Sec - Voltage (V) 36-50VDC

EMC Compliant (EN55015)

Power Factor Correction

0.5

Input Electrical Connections

Live, Unswitched Live, Neutral, Earth

Dimmable No

Emergency Data

Load Voltage 45VDC

Nominal Battery Current 1600mA

Recharge Time 24 hours

Battery Specification 1 x 3.2V 1.6Ah

Battery Type Li-ion(Lithium-ion)

Battery Total Weight 0.005kg
Battery Life In Emergency Mode 3 hours
Charge Current 200mA

DDP Protection Yes

LOR In Emergency Mode 13%

Inverter PFC

Thermals

Room Ambient Temperature 26°C

Performance Data

Lumens Per Circuit Watt

LED Life (Hours) 60000

Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

100

0.88

Energy Rating A+

Actual Lumen Output 1600

Standard Deviation Colour Matching - SDCM ≤ 6

Color Rendering Index 80-89

CRI: Ra **84**

Correlated Color Temperature 4000

Light Distribution Detail 116

LOR (Light Output Ratio) %

Controls and Sensors

Detection Distance 0.5-8m, adjustable

Detection Motion Speed $0.5-3 \, \text{m/s}$

Max. (Ø x h): 16m x 6m **Detection Range**

Installation Height 6m max

Detection Area 0.5-8m, adjustable

150°(Wall installation),360°(Ceiling installation) **Detection Angle**

5s | 30s | 60s | 3min | 5min | 10 min | 20 min | 30min Hold Time

2 lux | 10 lux | 25 lux | 50 lux | Disable Lux Settings

5.8GHz±75MHz, ISM wave band Microwave Frequency

Transmitting Power <0.5mW

Construction

Primary Material Polycarbonate

Outer Diffuser Polycarbonate

LED Brand **Nationstar**

PA6 Nylon Heat Sink

Polycarbonate **Driver Housing**

Packaging

Product Carton Dimensions 54 x 28 x 29cm

Product Packaged Weight 1.13

Quantity Per Outer Carton 8

54.0 Outer carton(L)-cm

28.0 Outer carton(W)- cm

Outer carton(H)- cm 29.0

Outer carton overall dimensions 54 x 28 x 29cm

Outer carton Net weight- kg 9.04kg

Outer carton Gross weight-kg 9.59kg

Product Bar Code EAN-13 Number 505254410655

Outer carton Bar Code ITF-14 Number 15052544106559

Standards & Approvals

Manufactured In Accordance To BS EN 60598-2-1

CE Marked Yes

Date code/Purchase order No. Yes

WEEE Symbol Yes

Certificate Of Conformity Available on request

Accredited Members LIA, ISO9001:2015, ISO14001:2015











JCC Lighting LTD Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex PO22 9TS Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 17 [08 Sep 2020]