# Product datasheet Characteristics

## EZ9E20MCU

## 20 way Metal Easy9 Consumer Unit



TTIGHT	
Range	Easy9
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Number of 18 mm modules per row	20
Provided equipment	Earth/Neutral terminal block Busbar

#### Complementary

		0
Enclosure mounting	Surface	
	Flush	eliability
Total number of 18 mm modules	20	0.1
Number of horizontal rows	1	— Suitability
Number of ways	20 ways	- ins
Enclosure material	Metal	—inim
Type of front cover	Plain	deter
[In] rated current	100 A	d for
[Ue] rated operational voltage	230/240 V	— es
Network frequency	50 Hz	
Type of rail	DIN	— s
Cable entry	Knock-out	r and
Cable cross section	125 mm² incoming	—ţi
Comb busbar and distribution block compatibility	YES	 
Product weight	7.03 kg	
Height	276.8 mm	    intende
Width	536.8 mm	— <u>i</u>
Depth	119.55 mm	<u>.s.</u>
Colour	White ( RAL 9003 )	_intatic
Product compatibility	Easy9 MCB Easy9 switch	  -
	Easy9 SPD Easy9 RCCB Easy9 RCBO	Jaimer: This

#### Environment

Standards	BS EN 61439-3 BS 7671: amendment 3	
IP degree of protection	IPxx D on top IP3x with cover	
IK degree of protection	IK05	
Overvoltage category	II .	