



### Main

Range	Acti 9
Product name	Load centre KQ II A
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Door Enclosure Front cover Pan assembly Shielded neutral bar suitable for 25 mm <sup>2</sup> Earth terminal block suitable for 25 mm <sup>2</sup>

### Complementary

Enclosure mounting	Surface
[Ie] rated operational current	125 A at 230/240 V AC
Incomer device	Switch disconnector - 2P Terminal block - 2P RCCB - 30 mA - 2P RCCB - 100 mA - 2P RCCB - 300 mA - 2P
Protection device type	Miniature circuit breaker (MCB) (plug-on type ) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type ) as outgoer
Number of ways	6 way(s) of 1P outgoer
Cable entry	Through knock-out at top and bottom Through knock-out at side
Height	270 mm
Width	266 mm
Depth	127 mm

### Environment

IP degree of protection	IP2x B internal confirming to BS EN 60529 IP3x external confirming to BS EN 60529
-------------------------	--

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications