

## www.hamilton-litestat.com

## Item Image Wiring **Dimensions** HARTLAND 1 GANG 20A DOUBLE POLE ROCKER SWITCH + NEON + CABLE OUTLET HARTLAND

## 77 DPNC BC-B

Hartland Bright Chrome 1 gang 20AX Double Pole Rocker and Neon and Cable Outlet. Standard Insert will be Bright Chrome with a Black surround.

Primary Range	Hartland	
Insert Type	Double Pole Rocker Switches with Neon and Cable Outlet	
Plate Finish	Bright Chrome	
Frame Finish	<u> </u>	
Switch Colour	Bright Chrome	
Body & Switch Trim	Black	
Height	Single = 88mm	
Width	Single = 88mm	
Depth	Single = 5mm	
Fixing Hole Centres	Box Fixing = 60.3mmBox Fixing = 60.3mm	
Minimum Wall Box Depth	35mm	
Wattage		
Switched Poles	Double	
Current Rating	20AX	
Voltage	220/250V AC	
Max load	20 Amp inductive	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3 x 2.5mm2	
Terminal Capacity 2	2 x 4mm2 Multi-Strand	
Terminal Capacity 3	1 x 6mm2	
Terminal Capacity 4		
Terminal Capacity 5		
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-Strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating	-5° to +40°C	
Temperature	5 15 15 5	
Recommended Location	Indoor use only	
Cable outlet (min)	0.75mm <sup>2</sup>	
Cable outlet (max)	2.5mm <sup>2</sup>	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	Trade Mark No. 2344778	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84







