



Fuse-link, low voltage, 2 A, AC 550 V, BS88, 21 x 129 mm, gL/gG, BS

AD2

Similar to illustration

Product name		Eaton Bussmann series low voltage British standard fuse
Part no.		AD2
EAN		5027590491754
Product Length/Depth		129 millimetre
Product height		21 millimetre
Product width		22 millimetre
Product weight		62.9 gram
Compliances		CE Marked RoHS Compliant
Certifications		BS88 IEC 60269 EAC
Product Tradename		None
Product Type		Low voltage British standard fuse
Product Sub Type		None
Globally Marketable		Yes

Voltage rating		550 V
Voltage type		AC
Breaking capacity		80 kA
Class		Class gG/gL

Application		general industrial applications
Fuse type		AD
Fitted with:		Centre bolted tags
Connection		111 mm fixing centre

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	550
Rated voltage DC	V	250
Rated current	A	2
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	1.2
Mounting holes		
Centre-to-centre distance of connections	mm	111