

PHOTOCELLS

ELECTRONIC REMOTE PHOTOCELL

Suitable for integration into luminaires or stand alone, our photocells all include a delay circuit to prevent nuisance switching.



Features

- Designed for use with LED loads
- All include a switching delay to prevent false switching due to headlights or cloud cover
- Provide automatic control dusk to dawn
- Deliver increased energy savings



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
PC25	Electronic Remote Photocell			400W	

Product Information

Guarantee	1 Year
IP Rating	IP65

Material (Body/Housing)	Polycarbonate
Approval	UKCA CE



PHOTOCELLS

ELECTRONIC REMOTE PHOTOCELL

Packaging Information

Dimensions (mm)	L: 53 x W: 45 x D: 30 mm x H: 19 x Ø: 20 mm
Product Net Weight (kg)	0.08 kg
Barcode	5055807609401
Box Dimensions (mm)	L: 70 x W: 70 x D: 70 mm
Box Gross Weight (kg)	0.09 kg

Units/Outer Carton	100
Outer Carton Barcode	15055807609408
Outer Carton Dimensions (mm)	L: 350 x W: 380 x D: 280 mm
Outer Carton Gross Weight (kg)	9.25 kg