

m10™ FIXED



IC COVER AVAILABLE SEPARATELY SEE TABLE BELOW FOR INFORMATION

DALI Dimmable
BUS+
Interface Module
See pg.246

Description



Fixed, integrated, fire rated 10W LED downlight with driver-on-board and high voltage, single source LED chip. Available in 2700K, 3000K and 4000K. Interchangeable bezels available in White, Matt White, Polished Chrome and Satin Nickel. Multiple lens options: 24°, 40° and 60°; 40° fitted as standard. Rated to 30, 60 and 90 minute fire ceilings. Complies with BS EN 1365-2:2000 (fire resistance), BS EN ISO 140-3: 1995 and BS EN ISO 140-6: 1998 (Acoustics), BS EN 13141-1:2400 (Air leakage).
5 year extended warranty - register at auroralighting.com/warranty




IP65 with the appropriate bezel - see table below
40° Lens supplied with luminaire as standard


HVLED iCDOB™




24° Lens



40° Lens



60° Lens




Specification			
Technology	LED	IP Rating	IP65 with bezel
Colour Rendering (Ra)	>80	Air Leakage	Yes
Luminaire Distribution	Direct	Fire Protection	Yes
Lifetime L70 (hrs)	40,000	Acoustic Rated	Yes
Input Voltage	220-240V	Operating Temp	25°C
Input Frequency (Hz)	50-60	Optic Material	PC
Dimmable	Yes	Power Factor	0.9
Dali	Dali Bus	SDCM	<6

SKU Code	Wattage	Luminous Flux	Efficacy LL/CW	Colour Temp (K)	Cutout (Ø)
Non-Dimmable					
AU-FRL801/30	10W	530lm	53	3000K	65mm
AU-FRL801/40	10W	550lm	55	4000K	65mm
Dimmable					
AU-FRLD811/27	10W	450lm	45	2700K	65mm
AU-FRLD811/30	10W	520lm	52	3000K	65mm
AU-FRLD811/40	10W	550lm	55	4000K	65mm



Bezel not included - see table below for details

SKU Code	Description	Bezel Colours
Bezel Options		
AU-BZ600*	m10™ Bezel 88mm Aluminium IP65	White
AU-BZ601*	m10™ Square Bezel 88mm Aluminium IP65	Matt White
AU-AP600*	m10™ Fire Rated Adaptor Plate Fixed 85-145mm	Polished Chrome
		Satin Nickel
AU-BZ603W	m10™ Fixed 88mm Polycarbonate Downlight Bezel Accessory	White
AU-BZ605W	m10™ Slimtrim Aluminium Bezel 90mm	White



(OD) 88mm Overall Ø
(RD) 95mm Recess Depth (Excluding IC cap)
(RD) 115mm Recess Depth (Including IC cap)

*Add Suffix **W, MW, PC or SN** to AU-BZ600, AU-BZ601, AU-AP600 for White, Matt White, Polished Chrome or Satin Nickel finishes

Lens Options

AU-LNM1024	Interchangeable 24 degree beam angle lens for m10™ downlight
AU-LNM1060	Interchangeable 60 degree beam angle lens for m10™ downlight

IC Cap

AU-ICC50	58mm Insulation Cover for m10™ Fixed Downlights
----------	---



AU-BZ605W slim trim bezel